PRODUCT RANGE SPECIFICATION

B22360(TG1-HLC) – Slop Hopper with High Level Cistern



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B22360(TG1-HLC){PSS}	14 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b22360tg1-hlc-slop-hopper-with-high-level-cistern#specifications

01 Product description and specification

Product description

Wall-mounted Grade 304 stainless steel slop hopper with a hinged bucket grid, high-level cistern, stainless steel flush pipe and pull-rod operation. Dimensions: 540mm (L) × 540mm (W) × 2321mm (overall height).

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B22360(TG1-HLC). Wall-mounted Grade 304 stainless steel slop hopper with a hinged bucket grid, high-level cistern, stainless steel flush pipe and pull-rod operation. Dimensions: 540mm (L) × 540mm (W) × 2321mm (overall height).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	540	mm	The length of the item typically as measured from left to right.
Width	540	mm	The width of the item typically as measured from front to back.
Height	2321	mm	Overall height of the complete unit.

03 Functional features

01 **Grade 304 stainless steel**
Pressed and welded stainless steel with a satin finish provides a smooth surface for routine cleaning.

02 **Hinged bucket grid**
The rear-hinged grid supports a bucket over the hopper and lifts to provide access for cleaning.

03 **High-level cistern with pull rod**

The cistern supplies stored flushing water to the hopper, with pull-rod operation.

04 **Wall-mounted installation**

Gallows brackets support the hopper and leave the floor beneath accessible for cleaning.

04 Application information

Intended applications	Hospital Sinks, Sluice Rooms (Dirty Utility Rooms)
Industries	Hospitals & Clinics

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

Where is this model used?

It is intended for waste disposal in healthcare and institutional sluice rooms, including hospital and clinic dirty utility rooms.

What flushing components are supplied?

The high-level cistern connects to the top-entry flush pipe and is operated by a pull rod. Stainless steel gallows brackets provide wall support.

What is the bucket grid for?

The hinged grid supports a bucket over the hopper and folds up to provide access for cleaning.

How is this hopper supported?

The hopper is wall mounted using stainless steel gallows brackets.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Product drawings and images



PRODUCT IMAGE

E&OE. Specifications are subject to change without notice.