

PRODUCT RANGE SPECIFICATION

B22360(TG1-HLC) – Slop Hopper with High Level Cistern



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
B22360(TG1-HLC){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
25 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.
<https://basterfield.co.za/products/b22360tg1-hlc-slop-hopper-with-high-level-cistern#specifications>



01 Product description and specification

Product description

Wall-mounted Grade 304 stainless steel slop hopper with a hinged bucket grid, high-level cistern, stainless steel flush pipe and pull-rod operation. Dimensions: 540mm (L) × 540mm (W) × 2321mm (overall height).

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B22360(TG1-HLC). Wall-mounted Grade 304 stainless steel slop hopper with a hinged bucket grid, high-level cistern, stainless steel flush pipe and pull-rod operation. Dimensions: 540mm (L) × 540mm (W) × 2321mm (overall height).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	540	mm	The length of the item typically as measured from left to right.
Width	540	mm	The width of the item typically as measured from front to back.
Height	2321	mm	Overall height of the complete unit.

03 Functional features

01 Grade 304 stainless steel

Pressed and welded stainless steel with a satin finish provides a smooth surface for routine cleaning.

02 Hinged bucket grid

The rear-hinged grid supports a bucket over the hopper and lifts to provide access for cleaning.

03 High-level cistern with pull rod

The cistern supplies stored flushing water to the hopper, with pull-rod operation.

04 Wall-mounted installation

Gallows brackets support the hopper and leave the floor beneath accessible for cleaning.

04 Application information

Intended applications	Hospital Sinks, Sluice Rooms (Dirty Utility Rooms)
Industries	Hospitals & Clinics

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.