
PRODUCT RANGE SPECIFICATION

B30428(120) – Recessed Security Toilet Roll Holder



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B30428(120){PSS}	14 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b30428120-recessed-security-toilet-roll-holder#specifications

01 Product description and specification

Product description	Recessed Grade 304 stainless steel toilet roll holder, 118 mm diameter × 110 mm deep, with 2 mm material and two threaded rods for through-wall fixing.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this product range. Basterfield B30428(120) recessed security toilet roll holder; Grade 304 stainless steel; material thickness 2 mm; diameter 118 mm; depth 110 mm; two 10 mm threaded rods for through-wall fixing.

02 Functional features

01 **Recessed Arrangement**
The holder is recessed and measures 118 mm in diameter and 110 mm deep.

02 **Grade 304 Stainless Steel**
The holder is manufactured from Grade 304 stainless steel with a material thickness of 2 mm.

03 **Through-Wall Fixing**
Two 10 mm threaded rods secure the holder through the wall.

03 Application information

Intended applications	Public Restrooms
Industries	Government & Public Sector

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

05 Frequently asked questions

What are the holder dimensions?

The holder measures 118 mm in diameter and 110 mm deep.

What material and thickness are specified?

The B30428(120) is manufactured from 2 mm thick Grade 304 stainless steel.

How is the holder fixed?

Two 10 mm threaded rods secure the recessed holder through the wall.

What should be coordinated before installation?

Coordinate the recessed position and access for the through-wall fixings with the wall construction.

E&OE. Specifications are subject to change without notice.