

MODEL SPECIFICATION

B34135(115-0545-SB-E-F) – Wash Trough Single Contractor
545mm Length

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B34135(115-0545-SB-E-F) {PSS}	Published catalogue data	30 Oct 2026

01 Model specification

Wash Trough, Stainless Steel Grade 304, 1.5mm Thickness, 545mm Length, with One Trough, Extended Splashback, Gallows Wall Brackets, Front Support Legs and Satin Brushed Finish

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	545	mm	The length of the item typically as measured from left to right.
Material Thickness	1.5	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Extended Splashback	Yes	–	–
Number of Troughs	1	–	–
Front Support Legs	Yes	–	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	545	mm

04 Model and supply data

Parent product	B34135(545) – Wall Mounted Single Contractor's Wash Trough
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B34135(115-0545-SB-E-F). Wash Trough, Stainless Steel Grade 304, 1.5mm Thickness, 545mm Length, with One Trough, Extended Splashback, Gallows Wall Brackets, Front Support Legs and Satin Brushed Finish.
Detailed specification	Stainless steel Grade 304; 1.5mm material thickness. 545mm length; 1 trough(s); 300mm trough depth. Extended Splashback. Gallows wall brackets. Front support legs. Wall-mounted, fully welded construction with radius-coved corners and a satin brushed finish. Suitable for wall-mounted tapware above the unit.

06 Frequently asked questions

What is the standard material and thickness?

The standard specification is Grade 430 stainless steel in 0.9mm thickness. Grade 304 and 1.2mm thickness are selectable standard options.

How do I select Grade 316 or 1.5mm thickness?

Open advanced customisations in the configuration selector. Grade 316 and any 1.5mm-thick configuration are advanced options.

What is included in the 545mm configurations?

The 545mm configurations have one trough, gallows wall brackets and a satin brushed finish. Every grade and thickness combination offers a standard or extended splashback and optional front support legs. Standard splashback and no front support legs are the default selections.

Are front support legs and an extended splashback optional on every model?

Yes. Choose Yes or No for front support legs and for an extended splashback. Either option can be selected independently, including both together, on every grade and thickness combination.

How do the single and double products differ?

The single has one trough and is 545mm long. The double has two troughs and is 1030mm long. Both have 300mm trough depth and the same material grade, thickness, splashback and front support leg choices. Prices are specific to each configuration.

Where is this wash trough used?

Typical applications include construction-site wash-up areas, workshops and industrial cleaning stations for mop rinsing, equipment washing and general cleaning.

What tap arrangement does it suit?

The trough suits wall-mounted tapware installed above the unit. Confirm the tapware and plumbing requirements for the installation.

How are prices and delivery handled?

Prices are shown for configurations with a confirmed selling price. Unpriced combinations show Price on request. Delivery is excluded.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.