

PRODUCT RANGE SPECIFICATION

B34135(545) – Wall Mounted Single Contractor’s Wash Trough



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
B34135(545){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
10 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

<https://basterfield.co.za/products/b34135545-wall-mounted-single-contractors-wash-trough#specifications>



01 Product description and specification

Product description

545mm wall-mounted single wash trough for construction sites, workshops and cleaning areas. Choose stainless steel grade, thickness, optional front support legs and an extended splashback.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Wall-mounted single contractors wash trough, 545mm length, with one trough, 300mm trough depth, fully welded construction, radius-coved corners, satin brushed finish and gallows wall brackets. Standard Grade 430 / 0.9mm; Grade 304 and 1.2mm options; Grade 316 and 1.5mm advanced customisations. Every configuration has independently selectable front support legs and standard or extended splashback options.

02 Models and configurations

Common to all models: Length: 545 mm · Number of Troughs: 1

ITEM CODE	MATERIAL	MATERIAL THICKNESS	EXTENDED SPLASHBACK	FRONT SUPPORT LEGS
B34135(109-0545-SB)	Stainless Steel Grade 304	0.9 mm	No	No
B34135(109-0545-SB-E)	Stainless Steel Grade 304	0.9 mm	Yes	No
B34135(109-0545-SB-E-F)	Stainless Steel Grade 304	0.9 mm	Yes	Yes
B34135(109-0545-SB-F)	Stainless Steel Grade 304	0.9 mm	No	Yes
B34135(112-0545-SB)	Stainless Steel Grade 304	1.2 mm	No	No
B34135(112-0545-SB-E)	Stainless Steel Grade 304	1.2 mm	Yes	No
B34135(112-0545-SB-E-F)	Stainless Steel Grade 304	1.2 mm	Yes	Yes
B34135(112-0545-SB-F)	Stainless Steel Grade 304	1.2 mm	No	Yes
B34135(115-0545-SB)	Stainless Steel Grade 304	1.5 mm	No	No
B34135(115-0545-SB-E)	Stainless Steel Grade 304	1.5 mm	Yes	No
B34135(115-0545-SB-E-F)	Stainless Steel Grade 304	1.5 mm	Yes	Yes

02 Models and configurations

Common to all models: Length: 545 mm · Number of Troughs: 1				
ITEM CODE	MATERIAL	MATERIAL THICKNESS	EXTENDED SPLASHBACK	FRONT SUPPORT LEGS
B34135(115-0545-SB-F)	Stainless Steel Grade 304	1.5 mm	No	Yes
B34135(209-0545-SB)	Stainless Steel Grade 430	0.9 mm	No	No
B34135(209-0545-SB-E)	Stainless Steel Grade 430	0.9 mm	Yes	No
B34135(209-0545-SB-E-F)	Stainless Steel Grade 430	0.9 mm	Yes	Yes
B34135(209-0545-SB-F)	Stainless Steel Grade 430	0.9 mm	No	Yes
B34135(212-0545-SB)	Stainless Steel Grade 430	1.2 mm	No	No
B34135(212-0545-SB-E)	Stainless Steel Grade 430	1.2 mm	Yes	No
B34135(212-0545-SB-E-F)	Stainless Steel Grade 430	1.2 mm	Yes	Yes
B34135(212-0545-SB-F)	Stainless Steel Grade 430	1.2 mm	No	Yes
B34135(215-0545-SB)	Stainless Steel Grade 430	1.5 mm	No	No
B34135(215-0545-SB-E)	Stainless Steel Grade 430	1.5 mm	Yes	No
B34135(215-0545-SB-E-F)	Stainless Steel Grade 430	1.5 mm	Yes	Yes
B34135(215-0545-SB-F)	Stainless Steel Grade 430	1.5 mm	No	Yes
B34135(309-0545-SB)	Stainless Steel Grade 316	0.9 mm	No	No
B34135(309-0545-SB-E)	Stainless Steel Grade 316	0.9 mm	Yes	No
B34135(309-0545-SB-E-F)	Stainless Steel Grade 316	0.9 mm	Yes	Yes
B34135(309-0545-SB-F)	Stainless Steel Grade 316	0.9 mm	No	Yes
B34135(312-0545-SB)	Stainless Steel Grade 316	1.2 mm	No	No
B34135(312-0545-SB-E)	Stainless Steel Grade 316	1.2 mm	Yes	No
B34135(312-0545-SB-E-F)	Stainless Steel Grade 316	1.2 mm	Yes	Yes
B34135(312-0545-SB-F)	Stainless Steel Grade 316	1.2 mm	No	Yes
B34135(315-0545-SB)	Stainless Steel Grade 316	1.5 mm	No	No
B34135(315-0545-SB-E)	Stainless Steel Grade 316	1.5 mm	Yes	No
B34135(315-0545-SB-E-F)	Stainless Steel Grade 316	1.5 mm	Yes	Yes
B34135(315-0545-SB-F)	Stainless Steel Grade 316	1.5 mm	No	Yes

03 Functional features

01	Wall-Mounted Installation Heavy-duty gallows wall brackets support the wash trough.
02	545mm Single Trough The 545mm-long unit has one trough for wash-up and cleaning tasks.
03	300mm Trough Depth Deep troughs provide space for washing equipment and rinsing mops.
04	Grade and Thickness Choices Grade 430 and 0.9mm are standard. Choose Grade 304 or 1.2mm options, with Grade 316 and 1.5mm under advanced customisations.
05	Welded Stainless Steel Construction Fully welded construction with radius-coved corners and a satin brushed finish.
06	Splashback and Support Options Choose a standard or extended splashback and add or omit front support legs on every published configuration. Both options can be selected independently.

04 Application information

Intended applications	Commercial Wash Troughs & Basins, General Handwashing, Hygienic Wash-Down & Cleaning
Industries	Construction, General Manufacturing, Government & Public Sector

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.