MODEL SPECIFICATION

B34655(SHROUD-109-2400) – Plumbing Shroud for B34655 2400mm Trough

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B34655(SHROUD-109-2400){PSS}	12 Nov 2026

01 Model specification

Plumbing Shroud Stainless Steel Grade 304 0.9mm Thickness 2356mm (L) x 594mm (H) x 200mm (D) with Wall Mounting Flange and Pre-Cut Mounting Holes Ø6mm for B34655 2400mm Wash Trough. Designed for a Basin Rim Height of 850mm Above Floor Level.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Depth (mm)	200	mm	–
Mounting Type	Wall Mounted	–	–
Compatible Trough Length	2400	mm	Nominal length of the wash trough that this component fits.
Length	2356	mm	The length of the item typically as measured from left to right.
Height	594	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Mounting Hole Diameter	6	mm	Diameter of the pre-cut mounting holes.
Required Basin Rim Height	850	mm	Required installation height from floor level to the rim of the compatible basin or trough.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	2356	mm
Width	200	mm
Overall height	594	mm

04 Model and supply data

Parent product	B34655(SHROUD-109) — Plumbing Shroud for B34655 Wash Troughs
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

Optional plumbing shroud for the 2400 mm B34655 wash trough, for concealing plumbing in pharmaceutical environments. The shroud mounts to the wall beneath the trough and extends partway underneath it.

Manufactured from 0.9 mm Grade 304 stainless steel, with overall dimensions of 2356 mm long × 594 mm high × 200 mm deep. The wall mounting flange has pre-cut Ø6 mm mounting holes.

Designed for installation with the basin rim 850 mm above floor level. The 2400 mm shroud fits the corresponding right-hand outlet B34655 trough with or without legs. Supplied as an optional extra; wash trough sold separately.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Plumbing Shroud Stainless Steel Grade 304 0.9mm Thickness 2356mm (L) x 594mm (H) x 200mm (D) with Wall Mounting Flange and Pre-Cut Mounting Holes Ø6mm for B34655 2400mm Wash Trough. Designed for a Basin Rim Height of 850mm Above Floor Level.

Detailed specification

Overall dimensions: 2356 mm (L) × 594 mm (H) × 200 mm (D).
Material: Grade 304 stainless steel, 0.9 mm thick.
Mounting: Wall mounting flange with Ø6 mm holes.
Compatible trough length: 2400 mm.
Required basin rim height above floor: 850 mm.

E&OE. Specifications are subject to change without notice.