

MODEL SPECIFICATION

**B34656(D-112-1800L) – Wall-Mounted 1.2 mm Grade 304 Stainless Steel Wash Trough with Knee-Operated Demand Valves and Uprand-Mounted Bib Spouts. Length: 1800 mm. Number of Stations: Three. Waste Outlet: Left Hand. Front Support Legs Included: No. Brushed Finish, Sloped Trough, Integral Uprand and Heavy-Duty Wall Brackets. Leg-Equipped Configurations Include 40 x 40 mm Square-Tube Grade 304 Stainless Steel Support Legs as Part of the Complete Trough.**

|                |                          |                          |              |
|----------------|--------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE       | DATA STATUS              | GENERATED ON |
| Model          | B34656(D-112-1800L){PSS} | Published catalogue data | 4 Oct 2026   |

01 Technical specifications

| PARAMETER                   | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                                                                                                               |
|-----------------------------|---------------------------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Length                      | 1800                      | mm   | Station count is matched to length: 1200 mm has two stations, 1800 mm has three stations, and 2400 mm has four stations.                                                                                     |
| Waste Outlet Diameter       | 40                        | mm   | —                                                                                                                                                                                                            |
| Front Support Legs          | No                        | —    | Support legs are optional but recommended when the unit is mounted to ISO panels without additional support, and for 2400 mm units. Select Yes to include legs as part of the complete trough configuration. |
| Number of Stations / Spouts | Three                     | —    | Station count is matched to length: 1200 mm has two stations, 1800 mm has three stations, and 2400 mm has four stations.                                                                                     |
| Waste Outlet Orientation    | Left Hand                 | —    | —                                                                                                                                                                                                            |
| Demand / Metered Valve      | Demand Valve              | —    | —                                                                                                                                                                                                            |
| Material                    | Stainless Steel Grade 304 | —    | The primary material used in the construction of the item. Certain components may be manufactured from different materials.                                                                                  |

01 Technical specifications

| PARAMETER          | VALUE | UNIT | TECHNICAL NOTE                                                                                                           |
|--------------------|-------|------|--------------------------------------------------------------------------------------------------------------------------|
| Material Thickness | 1.2   | mm   | The thickness of the material used for the item's primary construction. The thickness of individual components may vary. |

02 Model and supply data

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Parent product    | B34656 – Knee-Operated Stainless Steel Wash Trough with Upstand |
| Typical lead time | 10–15 working days                                              |
| Warranty          | 12 months                                                       |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.