

MODEL SPECIFICATION

B34660(DE-112-1200L) – Shrouded Wall-Mounted Knee-Operated Wash Trough with Upright and Bib Taps. Grade 304 Stainless Steel, 1.2 mm Construction. Length: 1200 mm. Washing Stations: Two. Waste Outlet: Left Hand. Front Support Legs Included: No. Demand-Valve Control.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B34660(DE-112-1200L){PSS}	Published catalogue data	4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1200	mm	1200 mm has two washing stations, 1800 mm has three, and 2400 mm has four. Station count is matched to length.
Number of Stations / Spouts	Two	—	1200 mm has two washing stations, 1800 mm has three, and 2400 mm has four. Station count is matched to length.
Waste Outlet Orientation	Left Hand	—	—
Front Support Legs	No	—	Front support legs are optional but recommended where units are mounted into ISO panels without additional support or for units 2400 mm in length. Select Yes to include front support legs.
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.

02 Model and supply data

Parent product	B34660 – Shrouded Knee-Operated Wash Trough with Upright and Bib Taps
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	Grade 304 stainless steel shrouded, wall-mounted knee-operated wash trough with 1.2 mm construction, upstand and bib taps. Length: 1200 mm. Washing stations: Two. Waste outlet: Left Hand. Front support legs included: No. Demand-valve control. Front support legs are optional but recommended where units are mounted into ISO panels without additional support or for units 2400 mm in length.
Detailed specification	Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Length: 1200 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Front Support Legs: No

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.