

MODEL SPECIFICATION

B34660(DE-112-2400L) – Shrouded Wall-Mounted Knee-Operated Wash Trough with Upright and Bib Taps. Grade 304 Stainless Steel, 1.2 mm Construction. Length: 2400 mm. Washing Stations: Four. Waste Outlet: Left Hand. Front Support Legs Included: No.

DOCUMENT SCOPE Model	DOCUMENT REFERENCE B34660(DE-112-2400L) {PSS}	DATA STATUS Published catalogue data	GENERATED ON 4 Oct 2026
-------------------------	---	---	----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	2400	mm	1200 mm has two washing stations, 1800 mm has three, and 2400 mm has four. Station count is matched to length.
Number of Stations / Spouts	Four	—	1200 mm has two washing stations, 1800 mm has three, and 2400 mm has four. Station count is matched to length.
Waste Outlet Orientation	Left Hand	—	—
Front Support Legs	No	—	Front support legs are optional but recommended where units are mounted into ISO panels without additional support or for units 2400 mm in length. Select Yes to include front support legs.
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.

02 Model and supply data

Parent product	B34660 – Shrouded Knee-Operated Wash Trough with Upright and Bib Taps
Typical lead time	10–15 working days

Warranty	12 months
----------	-----------

03 Specification notes

Configuration description	Grade 304 stainless steel shrouded, wall-mounted knee-operated wash trough with 1.2 mm construction, upstand and bib taps. Length: 2400 mm. Washing stations: Four. Waste outlet: Left Hand. Front support legs included: No. Front support legs are optional but recommended where units are mounted into ISO panels without additional support or for units 2400 mm in length.
Detailed specification	Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Length: 2400 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Front Support Legs: No

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.