

PRODUCT RANGE SPECIFICATION

B34660 – Knee Operated Wash Troughs

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B34660{PSS}	Published catalogue data	14 Sep 2026

01 Product description and specification

Product description	The B34660 is a shrouded, wall-mounted wash trough with knee-operated water control. It includes an upstand and bib taps. Select the required trough configuration to suit the number and arrangement of handwashing stations.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B34660. Knee Operated Wash Troughs. Length: 1200 mm, 1800 mm, 2400 mm. Waste Outlet Orientation: Left Hand, Right Hand. It includes an upstand and bib taps.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34660(DE-112-1200L)	Knee Operated Wash Trough to B34660{PSS} Stainless Steel Grade 304 with Demand Valve, Shroud and Upstand with BIB Taps 2 User 1200mm Length Left Hand Outlet Includes Front Support Legs	Length: 1200 mm Waste Outlet Orientation: Left Hand
B34660(DE-112-1200R)	Knee Operated Wash Trough to B34660{PSS} Stainless Steel Grade 304 with Demand Valve, Shroud and Upstand with BIB Taps 2 User 1200mm Length Right Hand Outlet Includes Front Support Legs	Length: 1200 mm Waste Outlet Orientation: Right Hand
B34660(DE-112-1800L)	B34660 Shrouded Wall Mounted Knee Operated Wash Trough With Upstand and Bib Taps Length: 1800. Waste Outlet Orientation: Left Hand.	Length: 1800 mm Waste Outlet Orientation: Left Hand
B34660(DE-112-1800R)	B34660 Shrouded Wall Mounted Knee Operated Wash Trough With Upstand and Bib Taps Length: 1800. Waste Outlet Orientation: Right Hand.	Length: 1800 mm Waste Outlet Orientation: Right Hand
B34660(DE-112-2400L)	B34660 Shrouded Wall Mounted Knee Operated Wash Trough With Upstand and Bib Taps Length: 2400. Waste Outlet Orientation: Left Hand.	Length: 2400 mm Waste Outlet Orientation: Left Hand

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34660(DE-112-2400R)	B34660 Shrouded Wall Mounted Knee Operated Wash Trough With Uprstand and Bib Taps Length: 2400. Waste Outlet Orientation: Right Hand.	Length: 2400 mm Waste Outlet Orientation: Right Hand

03 Application information

Intended applications	Hands-Free Handwashing (Knee/Elbow/Foot Operated)
Industries	Government & Public Sector

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.