MODEL SPECIFICATION

B34673(1200R) – Wash Trough 1200 mm, Right Hand, 50 mm, Legs No



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B34673(1200R){PSS}	13 Nov 2026

01 Model specification

Wall-Mounted Grade 304 Stainless Steel Wash Trough. Length: 1200 mm. Waste Outlet: Right Hand. Integral Splashback Height: 50 mm. Front Support Legs Included: No. Brushed Dull-Polish Finish, Sloped Base and Heavy-Duty Wall Brackets. For Wall-Mounted Bib Taps. The Optional B34674 Front Support Leg Set Uses 25 x 25 mm Grade 304 Stainless Steel Tube with Adjustable Feet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1200	mm	The length of the item typically as measured from left to right.
Waste Outlet Orientation	Right Hand	–	–
Splashback Height	50	mm	Height of the splashback above the tabletop or working surface.
Front Support Legs	No	–	–

03 Model and supply data

Parent product	B34673 — Wall-Mounted Stainless Steel Wash Trough
Typical lead time	10–15 working days
Warranty	12 months

04 Frequently asked questions

Which taps can be used with this wash trough?

The B34673 is designed for wall-mounted bib taps. It is not suitable for pillar tap installations.

What is the difference between the splashback options?

The standard integral splashback provides wall protection behind the trough. The extended option provides a taller splashback for additional wall coverage. The height of each option is shown under Splashback Height.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Are front support legs included?

Front support legs are included when Front Support Legs is set to Yes. These configurations use the -SL code suffix and include the B34674 Grade 304 stainless steel front support leg set with adjustable feet. Configurations set to No do not include the leg set.

Can I choose the waste outlet position?

Yes. Left-hand and right-hand waste outlets are available for each length, splashback and support-leg combination. A centre waste outlet is not offered in this range.

How is the trough mounted?

The trough is wall-mounted using the included heavy-duty wall brackets. Optional front support legs provide additional front support; the trough still requires its wall mounting.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357