

MODEL SPECIFICATION

**B34674(109-1800R-SL) – Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.**

|                |                               |                          |              |
|----------------|-------------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE            | DATA STATUS              | GENERATED ON |
| Model          | B34674(109-1800R-SL)<br>{PSS} | Published catalogue data | 4 Oct 2026   |

01 Technical specifications

| PARAMETER                | VALUE                   | UNIT | TECHNICAL NOTE                                                                                                                 |
|--------------------------|-------------------------|------|--------------------------------------------------------------------------------------------------------------------------------|
| Length                   | 1800                    | mm   | The length of the item typically as measured from left to right.                                                               |
| Waste Outlet Orientation | Right Hand              | –    | –                                                                                                                              |
| Extended Splashback      | No                      | –    | –                                                                                                                              |
| Front Support Legs       | Yes                     | –    | –                                                                                                                              |
| Material Thickness       | 0.91                    | mm   | The thickness of the material used for the item’s primary construction. The thickness of individual components may vary.       |
| Recommended User Spacing | 600                     | mm   | Recommended allowance of 600 mm per user for comfortable shoulder spacing. This is guidance, not a fixed tap or spout spacing. |
| Tap Hole Provision       | Not punched as standard | –    | Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.                          |

01 Technical specifications

| PARAMETER                | VALUE | UNIT | TECHNICAL NOTE                                                                                                                                                                                                                                              |
|--------------------------|-------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Indicative User Capacity | 3     | —    | Indicative user capacity = trough length divided by the recommended 600 mm per user. This is a planning guide, not a fixed number of stations, taps or spouts. Tap holes are not punched as standard; the final layout may accommodate more taps or spouts. |

02 Model and supply data

|                   |                                                                    |
|-------------------|--------------------------------------------------------------------|
| Parent product    | B34674 – Wall Mounted Stainless Steel Wash Trough with Tap Landing |
| Typical lead time | 10–15 working days                                                 |
| Warranty          | 12 months                                                          |

03 Specification notes

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration description | <p>Wall-mounted Grade 304 stainless steel wash trough with tap landing, 0.91 mm material thickness, 1800 mm length, right-hand waste outlet and standard 50 mm splashback. Includes front support legs made from 25 x 25 mm square tubular Grade 304 stainless steel with adjustable feet for levelling.</p> <p>Tap holes are not punched as standard. Indicative user capacity: 3 users, based on approximately 600 mm per user. This is a planning guide, not a fixed tap or spout count; the layout can accommodate more taps or spouts where required.</p>                                                                                                                                     |
| Short Form Specification  | <div><p><b>SPECIFICATION USE</b></p><p>Use this description when specifying this model.</p></div> <p>Basterfield B34674(109-1800R-SL). Wall-mounted Grade 304 stainless steel wash trough with tap landing, 0.91 mm material thickness, 1800 mm length, right-hand waste outlet and standard 50 mm splashback. Includes front support legs made from 25 x 25 mm square tubular Grade 304 stainless steel with adjustable feet for levelling.</p> <p>Tap holes are not punched as standard. Indicative user capacity: 3 users, based on approximately 600 mm per user. This is a planning guide, not a fixed tap or spout count; the layout can accommodate more taps or spouts where required.</p> |
| Detailed specification    | <ul style="list-style-type: none"><li>• Model: B34674(109-1800R-SL)</li><li>• Length: 1800 mm</li><li>• Waste Outlet Orientation: Right Hand</li><li>• Extended Splashback: No</li><li>• Front Support Legs: Yes</li><li>• Leg material: Grade 304 stainless steel</li><li>• Leg section: 25 x 25 mm square tube</li><li>• Feet: adjustable for levelling</li><li>• Material Thickness: 0.91 mm</li><li>• Tap Hole Provision: Not punched as standard</li><li>• Recommended User Spacing: 600 mm</li><li>• Indicative User Capacity: 3 users (length / 600 mm; guidance only, not a fixed tap or spout count)</li></ul>                                                                            |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.