

MODEL SPECIFICATION

B34674(109-2400L) – Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B34674(109-2400L){PSS}	Published catalogue data	4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	2400	mm	The length of the item typically as measured from left to right.
Waste Outlet Orientation	Left Hand	—	—
Extended Splashback	No	—	—
Front Support Legs	No	—	—
Material Thickness	0.91	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Recommended User Spacing	600	mm	Recommended allowance of 600 mm per user for comfortable shoulder spacing. This is guidance, not a fixed tap or spout spacing.
Tap Hole Provision	Not punched as standard	—	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Indicative User Capacity	4	—	Indicative user capacity = trough length divided by the recommended 600 mm per user. This is a planning guide, not a fixed number of stations, taps or spouts. Tap holes are not punched as standard; the final layout may accommodate more taps or spouts.

02 Model and supply data

Parent product	B34674 – Wall Mounted Stainless Steel Wash Trough with Tap Landing
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	Wall-mounted Grade 304 stainless steel wash trough with tap landing, 0.91 mm material thickness, 2400 mm length, left-hand waste outlet and standard 50 mm splashback. Front support legs are excluded; select the matching model with -SL inside the brackets to include legs. Tap holes are not punched as standard. Indicative user capacity: 4 users, based on approximately 600 mm per user. This is a planning guide, not a fixed tap or spout count; the layout can accommodate more taps or spouts where required.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B34674(109-2400L). Wall-mounted Grade 304 stainless steel wash trough with tap landing, 0.91 mm material thickness, 2400 mm length, left-hand waste outlet and standard 50 mm splashback. Front support legs are excluded; select the matching model with -SL inside the brackets to include legs. Tap holes are not punched as standard. Indicative user capacity: 4 users, based on approximately 600 mm per user. This is a planning guide, not a fixed tap or spout count; the layout can accommodate more taps or spouts where required.
Detailed specification	• Model: B34674(109-2400L) • Length: 2400 mm • Waste Outlet Orientation: Left Hand • Extended Splashback: No • Front Support Legs: No (excluded) • Material Thickness: 0.91 mm • Tap Hole Provision: Not punched as standard • Recommended User Spacing: 600 mm • Indicative User Capacity: 4 users (length / 600 mm; guidance only, not a fixed tap or spout count)

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.