MODEL SPECIFICATION

B34674(109-1200L) – Wash Trough 1200mm Left-Hand Standard

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B34674(109-1200L){PSS}	13 Nov 2026

01 Model specification

Wall-Mounted Wash Trough Grade 304 Stainless Steel 0.91mm, 1200mm Length, with Tap Landing, Left-Hand Waste Outlet and Standard 50mm Splashback. Front support legs are excluded; select the matching model with -SL inside the brackets to include legs. Tap holes are not punched as standard. Indicative capacity: 2 users at approximately 600mm per user. This is a planning guide, not a fixed tap or spout count; more taps or spouts may fit depending on the layout.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1200	mm	The length of the item typically as measured from left to right.
Waste Outlet Orientation	Left Hand	–	–
Extended Splashback	No	–	–
Front Support Legs	No	–	–
Material Thickness	0.91	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Recommended User Spacing	600	mm	Recommended allowance of 600 mm per user for comfortable shoulder spacing. This is guidance, not a fixed tap or spout spacing.
Tap Hole Provision	Not punched as standard	–	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.
Width	390	mm	Overall trough width measured from front to back.
Tapware Landing	80	mm	Front-to-back dimension of the rear landing for deck-mounted tapware. Tap holes are not punched as standard.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Indicative User Capacity	2	—	Indicative user capacity = trough length divided by the recommended 600 mm per user. This is a planning guide, not a fixed number of stations, taps or spouts. Tap holes are not punched as standard; the final layout may accommodate more taps or spouts.

03 Model and supply data

Parent product	B34674 — Wall Mounted Stainless Steel Wash Trough with Tap Landing
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

This 1200mm B34674 wash trough has a tap landing, a left-hand waste outlet and a standard 50mm splashback. It is designed for wall mounting and manufactured from 0.91mm Grade 304 stainless steel.

Front support legs are excluded; select the matching model with -SL inside the brackets to include legs.

Tap holes are not punched as standard. Indicative capacity: 2 users at approximately 600mm per user. This is a planning guide, not a fixed tap or spout count; more taps or spouts may fit depending on the layout.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B34674(109-1200L). Wall-Mounted Wash Trough Grade 304 Stainless Steel 0.91mm, 1200mm Length, with Tap Landing, Left-Hand Waste Outlet and Standard 50mm Splashback. Front support legs are excluded; select the matching model with -SL inside the brackets to include legs. Tap holes are not punched as standard. Indicative capacity: 2 users at approximately 600mm per user. This is a planning guide, not a fixed tap or spout count; more taps or spouts may fit depending on the layout.

Detailed specification

- Model: B34674(109-1200L)
- Mounting: Wall mounted
- Material: Grade 304 stainless steel
- Material thickness: 0.91mm
- Length: 1200mm
- Waste outlet orientation: Left hand
- Tap landing: For deck-mounted tapware
- Tap hole provision: Not punched as standard
- Splashback: Standard 50mm
- Front support legs: Excluded
- Recommended user spacing: Approximately 600mm
- Indicative user capacity: 2 users; guidance only, not a fixed tap or spout count

05 Frequently asked questions

What material and thickness is the B34674 made from?

The B34674 is manufactured from 0.91mm Grade 304 stainless steel, with welded construction and a brushed dull-polish finish. The trough basin slopes towards the selected waste outlet.

Which lengths and configurations are available?

Choose 1200mm, 1800mm or 2400mm length, a left- or right-hand waste outlet, a standard or extended splashback, and front support legs with Yes or No. These choices give 24 configurations. The standard splashback is 50mm high; confirm the height required for an extended splashback when requesting a quotation.

What type of taps can be used on the tap landing?

The 80mm rear tap landing is intended for deck-mounted tapware, such as pillar taps or deck-mounted spouts. Confirm the tap or spout model, hole size, spacing and plumbing arrangement before ordering. Agree the required tapware and plumbing components as part of the quotation.

Are tap holes punched as standard?

No. Tap holes are not punched as standard. The product images illustrate a possible tap layout and show holes; they do not define the standard drilling provision. Confirm the required hole positions and sizes for the chosen tapware.

How many people can use each trough?

For planning, allow approximately 600mm per user: about 2 users at 1200mm, 3 at 1800mm and 4 at 2400mm. This is indicative guidance, not a fixed number of taps or spouts. More taps or spouts may fit depending on their spacing and the intended layout.

Can I choose the waste outlet position?

Yes. Left-hand and right-hand waste outlet configurations are available. The published outlet size is 40mm. The waste centre is 125mm from the selected outlet end and 219mm from the rear edge. Choose the position to suit the drainage layout and confirm the waste fitting, trap and pipework required for the installation.

Are front support legs included?

Front support legs are included only when Front Support Legs: Yes is selected. These complete trough configurations have -SL inside the item-code brackets. The legs are made from 25 × 25mm square tubular Grade 304 stainless steel and have adjustable feet for levelling. Models with Front Support Legs: No exclude the legs.

Does a model with front support legs still mount to the wall?

Yes. B34674 is a wall-mounted trough, including when front support legs are selected. Wall installation uses heavy-duty mounting brackets. Confirm the wall construction, bracket fixing method, installation height and any additional support requirements for the site. The trough is 390mm wide. The standard 50mm splashback model without legs measures 401mm overall vertically, including the wall brackets and splashback; this is not the height above the floor.

Why do some configurations require a quotation?

Standard splashback configurations have published prices excluding VAT. Extended splashback configurations require a quotation. Select the required length, waste outlet position and front support leg option, then confirm the extended splashback height and tap layout with Basterfield.

Which related wash troughs should I compare?

Compare B34673 for a trough designed for wall-mounted bib taps, B34672 for a splash-reducing front face, B34655 for a shrouded knee-operated trough, or B34756 for a rear upstand designed to house sensor tap electronics. These are separate products with their own specifications; links are in Related products.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357