

PRODUCT RANGE SPECIFICATION

B34674 – Wall Mounted Stainless Steel Wash Trough with Tap Landing



PRODUCT IMAGE · Illustrative product view. Tap holes are not punched as standard.

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B34674{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

24 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/b34674-wall-mounted-stainless-steel-wash-trough-with-tap-landing#specifications>



01 Product description and specification

Product description

Wall-mounted wash trough in 0.91mm Grade 304 stainless steel, with a rear landing for deck-mounted tapware. Choose 1200, 1800 or 2400mm, a left- or right-hand waste outlet, standard or extended splashback, and optional front support legs. Tap holes are not punched as standard.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B34674 wall-mounted wash trough with rear tap landing. Welded 0.91mm Grade 304 stainless steel; brushed dull-polish finish; sloped basin; 40mm left- or right-hand waste outlet. Lengths: 1200mm, 1800mm or 2400mm. Standard integral splashback: 50mm; extended splashback available by quotation with height to be confirmed. Tap holes are not punched as standard. Optional front support legs: 25 × 25mm square tubular Grade 304 stainless steel with adjustable feet, included in -SL configurations. Wall mounting uses heavy-duty brackets. Indicative capacity at approximately 600mm per user: 2, 3 or 4 users respectively; tap and spout counts depend on the chosen layout. Confirm tapware, drilling, plumbing and site fixing requirements when ordering. The trough is 390mm wide from front to back, with an 80mm rear tap landing. The waste centre is 125mm from the selected outlet end and 219mm from the rear edge. The front-view dimension from tap-landing level to the low end of the basin is 152mm. For the standard 50mm splashback configuration without front support legs, the overall vertical envelope is 401mm including the wall brackets and splashback. This is the product envelope, not the installation height above the floor. Extended splashbacks and front support legs change the overall height; confirm their required dimensions separately.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Recommended User Spacing	600	mm	Recommended allowance of 600 mm per user for comfortable shoulder spacing. This is guidance, not a fixed tap or spout spacing.
Tap Hole Provision	Not punched as standard	—	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.
Width	390	mm	Overall trough width measured from front to back.
Tapware Landing	80	mm	Front-to-back dimension of the rear landing for deck-mounted tapware. Tap holes are not punched as standard.
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Configuration options

Length	1200 mm; 1800 mm; 2400 mm
Waste Outlet Orientation	Left Hand; Right Hand
Extended Splashback	No; Yes
Front Support Legs	No; Yes

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01	Grade 304 Stainless Steel Welded 0.91mm Grade 304 stainless steel construction with a brushed dull-polish finish.
02	Landing for Deck-Mounted Tapware The 80mm rear landing accommodates pillar taps or deck-mounted spouts. Tap holes are not punched as standard, so the layout can be agreed for the selected tapware.
03	Three Trough Lengths Choose a 1200mm, 1800mm or 2400mm trough to suit the available wall space and handwashing layout.
04	Left- or Right-Hand Drainage The sloped basin directs water towards the 40mm waste outlet. Select the outlet position to suit the planned drainage connection.
05	Standard or Extended Splashback A 50mm integral splashback is standard. Extended splashback configurations are available by quotation; confirm the required height when ordering.
06	Optional Front Support Legs Select Front Support Legs: Yes for 25 × 25mm square tubular Grade 304 stainless steel legs with adjustable feet. The legs form part of the selected -SL configuration.
07	Flexible Tap Layout Allow approximately 600mm per user as a planning guide: about 2, 3 or 4 users across the three lengths. Tap and spout counts depend on the chosen layout.

Intended applications	Commercial Wash Troughs & Basins, General Handwashing, Public Restrooms
Industries	General Manufacturing, Government & Public Sector, Schools

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE · Illustrative product view. Tap holes are not punched as standard.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.