

PRODUCT RANGE SPECIFICATION

B34674 – Wall Mounted Stainless Steel Wash Trough with Tap Landing



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B34674{PSS}	Published catalogue data	4 Oct 2026

01 Product description and specification

Product description

Wall-mounted stainless steel wash trough with a tap landing for shared handwashing areas in commercial and institutional facilities.

It is designed for commercial projects and high use areas such as educational institutions, factories and public amenities. The wall mounted wash trough is supplied with an integral splashback which assists in keeping the washroom area clean. The splashback is 50 mm high as standard but can be manufactured with an extended splashback as optional. The stainless steel wash trough is manufactured from Grade 304 stainless steel. The unit features a brushed dull polish finish which is both aesthetic and highly hygienic.

The trough basin of the B34674 Wall Mounted stainless steel Wash Trough With Tap Landing is designed with the requisite fall to ensure efficient drainage of water. The water is drained from the unit via the waste outlet which can be orientated either left-hand or right-hand. The wash trough is suitable for deck mounted tapware such as pillar taps or spouts. As the wash trough is suitable for handling high volume use, it is more cost-effective than traditional basins. The stainless steel wash trough is available in a choice of lengths to suit the required installation and tap layout. Tap holes are not punched as standard.

Construction and features

- Wall mounted wash trough with tap landing.
- Features an integral stainless steel splashback which assists in keeping the washroom area clean.
- The splashback is 50 mm high as standard but an extended splashback is available as optional.
- A fully-welded, one-piece construction results in a robust and long-lasting product.
- Manufactured from Grade 304 stainless steel.
- The stainless steel prevents rust and corrosion and makes the wash trough extremely easy to clean and maintain.
- The trough-like basin is sloped to ensure efficient and hygienic drainage.
- The wash trough is easily installed with heavy duty wall mounting brackets.
- The wall mounted wash trough is designed for use with deck mounted tapware – for example, pillar taps.
- Supplied with a 40 mm waste outlet that can be configured as left-hand or right-hand.
- Perfectly suited for use in high demand areas where a number of users require washing facilities at the same time.

Available with or without front support legs. Models with -SL inside the specification brackets, such as B34674(109-1200L-SL), include 25 x 25 mm square tubular Grade 304 stainless steel front support legs with adjustable feet for levelling. Select Front Support Legs: Yes for the complete leg-equipped trough.

Material thickness: 0.91 mm. Published prices exclude VAT.

Tap holes are not punched as standard. We recommend allowing approximately 600 mm per user for comfortable shoulder spacing. Indicative user capacity is calculated from trough length divided by 600 mm: approximately 2 users at 1200 mm, 3 at 1800 mm and 4 at 2400 mm. This is a planning guide, not a fixed tap or spout count; a 1200 mm trough may accommodate more taps or spouts depending on the chosen layout.

Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B34674. Wall Mounted Stainless Steel Wash Trough With Tap Landing. Length: 1200 mm, 1800 mm, 2400 mm. Waste Outlet Orientation: Left Hand, Right Hand. Extended Splashback: No, Yes. The splashback is 50 mm high as standard but can be manufactured with an extended splashback as optional. The splashback is 50 mm high as standard but an extended splashback is available as optional. Available with or without front support legs. Models with -SL inside the specification brackets, such as B34674(109-1200L-SL), include 25 x 25 mm square tubular Grade 304 stainless steel front support legs with adjustable feet for levelling. Select Front Support Legs: Yes for the complete leg-equipped trough. Material thickness: 0.91 mm. Published prices exclude VAT. Tap holes are not punched as standard. We recommend allowing approximately 600 mm per user for comfortable shoulder spacing. Indicative user capacity is calculated from trough length divided by 600 mm: approximately 2 users at 1200 mm, 3 at 1800 mm and 4 at 2400 mm. This is a planning guide, not a fixed tap or spout count; a 1200 mm trough may accommodate more taps or spouts depending on the chosen layout.
--------------------------	--

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Recommended User Spacing	600	mm	Recommended allowance of 600 mm per user for comfortable shoulder spacing. This is guidance, not a fixed tap or spout spacing.
Tap Hole Provision	Not punched as standard	—	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(109-1200L)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: No Length: 1200 mm Waste Outlet Orientation: Left Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(109-1200L-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: Yes Length: 1200 mm Waste Outlet Orientation: Left Hand
B34674(109-1200R)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: No Length: 1200 mm Waste Outlet Orientation: Right Hand
B34674(109-1200R-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: Yes Length: 1200 mm Waste Outlet Orientation: Right Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(109-1800L)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: No Length: 1800 mm Waste Outlet Orientation: Left Hand
B34674(109-1800L-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: Yes Length: 1800 mm Waste Outlet Orientation: Left Hand
B34674(109-1800R)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: No Length: 1800 mm Waste Outlet Orientation: Right Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(109-1800R-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: Yes Length: 1800 mm Waste Outlet Orientation: Right Hand
B34674(109-2400L)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: No Length: 2400 mm Waste Outlet Orientation: Left Hand
B34674(109-2400L-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Left-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: Yes Length: 2400 mm Waste Outlet Orientation: Left Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(109-2400R)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: No Length: 2400 mm Waste Outlet Orientation: Right Hand
B34674(109-2400R-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Right-Hand Waste Outlet and Standard 50 mm Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: No Front Support Legs: Yes Length: 2400 mm Waste Outlet Orientation: Right Hand
B34674(E-109-1200L)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Left-Hand Waste Outlet and Extended Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: No Length: 1200 mm Waste Outlet Orientation: Left Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(E-109-1200L-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Left-Hand Waste Outlet and Extended Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: Yes Length: 1200 mm Waste Outlet Orientation: Left Hand
B34674(E-109-1200R)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Right-Hand Waste Outlet and Extended Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: No Length: 1200 mm Waste Outlet Orientation: Right Hand
B34674(E-109-1200R-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1200 mm Length, Right-Hand Waste Outlet and Extended Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 2 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: Yes Length: 1200 mm Waste Outlet Orientation: Right Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(E-109-1800L)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Left-Hand Waste Outlet and Extended Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: No Length: 1800 mm Waste Outlet Orientation: Left Hand
B34674(E-109-1800L-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Left-Hand Waste Outlet and Extended Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: Yes Length: 1800 mm Waste Outlet Orientation: Left Hand
B34674(E-109-1800R)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Right-Hand Waste Outlet and Extended Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: No Length: 1800 mm Waste Outlet Orientation: Right Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(E-109-1800R-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 1800 mm Length, Right-Hand Waste Outlet and Extended Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 3 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: Yes Length: 1800 mm Waste Outlet Orientation: Right Hand
B34674(E-109-2400L)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Left-Hand Waste Outlet and Extended Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: No Length: 2400 mm Waste Outlet Orientation: Left Hand
B34674(E-109-2400L-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Left-Hand Waste Outlet and Extended Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: Yes Length: 2400 mm Waste Outlet Orientation: Left Hand

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34674(E-109-2400R)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Right-Hand Waste Outlet and Extended Splashback. Front Support Legs Are Excluded; Select the Matching Model with -SL Inside the Brackets to Include Legs. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: No Length: 2400 mm Waste Outlet Orientation: Right Hand
B34674(E-109-2400R-SL)	Wall-Mounted Grade 304 Stainless Steel Wash Trough with Tap Landing, 0.91 mm Material Thickness, 2400 mm Length, Right-Hand Waste Outlet and Extended Splashback. Includes Front Support Legs Made from 25 x 25 mm Square Tubular Grade 304 Stainless Steel with Adjustable Feet for Levelling. Tap Holes Are Not Punched as Standard. Indicative User Capacity: 4 Users, Based on Approximately 600 mm per User. This Is a Planning Guide, Not a Fixed Tap or Spout Count; the Layout Can Accommodate More Taps or Spouts Where Required.	Extended Splashback: Yes Front Support Legs: Yes Length: 2400 mm Waste Outlet Orientation: Right Hand

04 Application information

Intended applications	Commercial Wash Troughs & Basins, General Handwashing
Industries	Government & Public Sector

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images**PRODUCT IMAGE**

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.