MODEL SPECIFICATION

B34676(115-2400LL) – Wash Trough Shrouded Left-Hand Waste 2400mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B34676(115-2400LL){PSS}	Published catalogue data	17 Oct 2026

01 Model specification

Wash Trough Neutral-Type Stainless Steel Grade 304 1.5mm Thick, 2400mm Length, Four Stations, with Wall Mounting, Shroud, Tap Landing and Left-Hand Waste Outlet, with Front Support Legs. Tapware, Knee-Operated Controls and Pre-Punched Tap Holes Excluded

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	2400	mm	The length of the item typically as measured from left to right.
Number of Stations / Spouts	Four	–	–
Waste Outlet Orientation	Left Hand	–	–
Front Support Legs	Yes	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.5	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Tap Hole Provision	Not punched as standard	–	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	2400	mm

04 Model and supply data

Parent product	B34676 – Shrouded Wash Trough with Tap Landing
Typical lead time	10–15 working days
Warranty	12 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

05 Specification notes

Configuration description	Wall-mounted shrouded wash trough for personnel handwashing in food hygiene environments. The tap landing accommodates pillar taps, or specify a bib-tap installation above the trough. Tapware and pre-punched tap holes are excluded as standard. Optional sensor taps provide hands-free operation; B34655 offers knee operation. Front support legs supplement wall mounting.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this model. Wash Trough Neutral-Type Stainless Steel Grade 304 1.5mm Thick, 2400mm Length, Four Stations, with Wall Mounting, Shroud, Tap Landing and Left-Hand Waste Outlet, with Front Support Legs. Tapware, Knee-Operated Controls and Pre-Punched Tap Holes Excluded.
Detailed specification	Length: 2400mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Front Support Legs: Yes Material: Stainless Steel Grade 304 Material Thickness: 1.5mm Tap Hole Provision: Not punched as standard Tapware: Supplied Separately Knee-Operated Controls: Not Included

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Product drawings and images

ISOMETRIC VIEW · 1200mm right-hand model shown without support legs. Tap holes are illustrated; pre-punched tap holes are not included as standard. Configurations vary.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357