

PRODUCT RANGE SPECIFICATION

B34676 – Shrouded Wash Trough with Tap Landing

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE B34676{PSS}	DATA STATUS Published catalogue data	GENERATED ON 17 Oct 2026
---------------------------------	-----------------------------------	---	-----------------------------

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

<https://basterfield.co.za/products/b34676-shrouded-wash-trough-with-tap-landing#specifications>



01 Product description and specification

Product description	Wall-mounted Grade 304 stainless steel wash trough with a shroud and tap landing for pillar tapware, also suitable for a bib-tap installation. Choose 1200mm with two stations, 1800mm with three or 2400mm with four; left or right waste outlet; and optional front support legs. Tapware and pre-punched tap holes are excluded as standard. Optional Cobra sensor taps provide hands-free operation.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Wall-Mounted Shrouded Wash Trough in Grade 304 Stainless Steel with Tap Landing. Length 1200mm or 1800mm in 1.2mm Thickness, or 2400mm in 1.5mm Thickness; Two, Three or Four Washing Stations Respectively; Left-Hand or Right-Hand Waste Outlet; Optional Front Support Legs. Tapware, Knee-Operated Controls and Pre-Punched Tap Holes Excluded as Standard.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Tap Hole Provision	Not punched as standard	–	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.

03 Models and configurations

ITEM CODE	LENGTH	NUMBER OF STATIONS / SPOUTS	WASTE OUTLET ORIENTATION	FRONT SUPPORT LEGS	MATERIAL THICKNESS
B34676(112-1200L)	1200 mm	Two	Left Hand	No	1.2 mm
B34676(112-1200LL)	1200 mm	Two	Left Hand	Yes	1.2 mm
B34676(112-1200R)	1200 mm	Two	Right Hand	No	1.2 mm
B34676(112-1200RL)	1200 mm	Two	Right Hand	Yes	1.2 mm
B34676(112-1800L)	1800 mm	Three	Left Hand	No	1.2 mm

03 Models and configurations

ITEM CODE	LENGTH	NUMBER OF STATIONS / SPOUTS	WASTE OUTLET ORIENTATION	FRONT SUPPORT LEGS	MATERIAL THICKNESS
B34676(112-1800LL)	1800 mm	Three	Left Hand	Yes	1.2 mm
B34676(112-1800R)	1800 mm	Three	Right Hand	No	1.2 mm
B34676(112-1800RL)	1800 mm	Three	Right Hand	Yes	1.2 mm
B34676(115-2400L)	2400 mm	Four	Left Hand	No	1.5 mm
B34676(115-2400LL)	2400 mm	Four	Left Hand	Yes	1.5 mm
B34676(115-2400R)	2400 mm	Four	Right Hand	No	1.5 mm
B34676(115-2400RL)	2400 mm	Four	Right Hand	Yes	1.5 mm

04 Functional features

01	Shrouded Construction The stainless steel shroud conceals plumbing beneath the wall-mounted trough.
02	Tap Landing Accommodates pillar taps and a suitable bib-tap installation above the trough. Tapware and pre-punched holes are excluded as standard.
03	Grade 304 Stainless Steel 1.2mm construction for 1200mm and 1800mm models; 1.5mm for the 2400mm model.
04	Two to Four Washing Stations Choose 1200mm with two stations, 1800mm with three or 2400mm with four.
05	Outlet and Support Options Choose a left-hand or right-hand waste outlet, with optional front support legs on every model.
06	Optional Sensor Tapware Cobra Cobratron EL-1000 sensor pillar taps are available separately for hands-free handwashing.

05 Application information

Intended applications	Commercial Wash Troughs & Basins, General Handwashing
Industries	Food & Beverage Processing

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images

ISOMETRIC VIEW · 1200mm right-hand model shown without support legs. Tap holes are illustrated; pre-punched tap holes are not included as standard. Configurations vary.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.