

MODEL SPECIFICATION

**B34756(S-109-1800R) – Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.**

|                |                          |                          |              |
|----------------|--------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE       | DATA STATUS              | GENERATED ON |
| Model          | B34756(S-109-1800R){PSS} | Published catalogue data | 4 Oct 2026   |

01 Technical specifications

| PARAMETER                   | VALUE                                                                                                                                          | UNIT | TECHNICAL NOTE                                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------------------------------------------------------------------------------------------------------------|
| Length                      | 1800                                                                                                                                           | mm   | The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four.                                 |
| Rear Uprand Design          | Wide rear uprand with space for sensor tap electronics                                                                                         | —    | —                                                                                                                     |
| Number of Stations / Spouts | Three                                                                                                                                          | —    | The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four.                                 |
| Tap Hole Provision          | Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the uprand is supplied without pre-punched tap holes. | —    | Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.                 |
| Mounting Type               | Wall Mounted with Gallows Brackets                                                                                                             | —    | —                                                                                                                     |
| Waste Outlet Orientation    | Right Hand                                                                                                                                     | —    | —                                                                                                                     |
| Front Support Legs          | No                                                                                                                                             | —    | Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units. Add R1,934 ex VAT per trough. |
| Tapware Supply              | Optional Sensor Tapware or Standard Bib Taps; Priced Separately                                                                                | —    | —                                                                                                                     |

01 Technical specifications

| PARAMETER          | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                                                        |
|--------------------|---------------------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material Thickness | 0.9                       | mm   | Standard: 0.9 mm. The 1.2 mm trough costs 33% more; 1.5 mm costs a further 25% more than 1.2 mm.                                                      |
| Material           | Stainless Steel Grade 304 | —    | The Grade 316 option applies to contact surfaces and adds 50% to the trough price for the selected thickness. Optional support legs remain Grade 304. |

02 Dimensions and mass

| PARAMETER | VALUE | UNIT |
|-----------|-------|------|
| Length    | 1800  | mm   |

03 Model and supply data

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Parent product    | B34756 – Stainless Steel Wash Trough with Sensor Tap Upstand |
| Typical lead time | 10–15 working days                                           |
| Warranty          | 12 months                                                    |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.