
PRODUCT RANGE SPECIFICATION

B34756 – Stainless Steel Wash Trough with Sensor Tap Upstand



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B34756{PSS}	15 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b34756-stainless-steel-wash-trough-with-upstand-for-bib-taps#specifications

01 Product description and specification

Product description

Stainless steel wash trough with a wide rear upstand designed to house sensor tap electronics. Suitable for sensor taps or standard bib taps, with pre-punched tap holes when tapware is specified or supplied. Choose 1200, 1800 or 2400 mm, left- or right-hand waste outlet, and optional support legs. Standard 0.9 mm Grade 304; thicker material and Grade 316 contact surfaces are available as advanced options. Tapware is priced separately.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B34756 wall-mounted stainless steel wash trough with wide rear upstand for sensor tap electronics, gallows brackets and sloped basin. The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four. Left- or right-hand waste outlet. Standard 0.9 mm Grade 304; 1.2 mm, 1.5 mm and Grade 316 contact surfaces optional. Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes. Tapware priced separately. Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Rear Upstand Design	Wide rear upstand with space for sensor tap electronics	–	–
Tap Hole Provision	Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes.	–	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.
Mounting Type	Wall Mounted with Gallows Brackets	–	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Tapware Supply	Optional Sensor Tapware or Standard Bib Taps; Priced Separately	–	–

03 Configuration options

Length	1200 mm; 1800 mm; 2400 mm
Number of Stations / Spouts	Four; Three; Two
Waste Outlet Orientation	Left Hand; Right Hand
Front Support Legs	No; Yes

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 Wide Upstand for Sensor Electronics
The wide rear upstand provides space to house the electronics for sensor tapware.

02 Sensor or Standard Bib Taps
Specify optional Cobra Cobratron sensor taps or use standard bib taps to suit the installation.

03 Tap Holes Matched to Specified Tapware
Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes.

04 Two, Three or Four Washing Stations
The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four.

05 Optional Stainless Steel Support Legs
Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units. The option adds R1,934 ex VAT per trough.

06 Material Options
Standard 0.9 mm Grade 304 stainless steel, with 1.2 mm and 1.5 mm thicknesses and Grade 316 contact surfaces available under advanced customisation.

07 Outlet Options and Sloped Basin
Choose a left-hand or right-hand waste outlet. The sloped basin directs water towards the outlet.

05 Application information

Intended applications	Commercial Wash Troughs & Basins, General Handwashing, Hands-Free Handwashing, Pharmaceutical Support Areas
Industries	Food & Beverage Processing, General Manufacturing, Government & Public Sector, Pharmaceutical Manufacturing

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

07 Frequently asked questions

What is the wide rear upstand for?
It provides the tap mounting face and enough space behind it to house sensor tap electronics.

Are tap holes pre-punched?

Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes.

Are taps included in the trough price?

No. Tapware is priced separately. The recommended tap is the Cobra Cobratron 04TSEN-COB-EL-1002-C. Select one tap per washing station.

Can I use standard bib taps instead?

Yes. The trough can be used with standard bib taps instead of sensor taps. Specify the tapware so the tap holes can be prepared to suit.

How many taps do I need?

The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four. The recommended quantity is one tap per station.

When should I select support legs?

Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units. Legs cost R1,934 ex VAT per trough. The unit still requires wall mounting.

What do the advanced material options change?

The 1.2 mm trough costs 33% more than the standard 0.9 mm trough; 1.5 mm costs a further 25% more than 1.2 mm. Grade 316 contact surfaces cost 50% more than Grade 304 at the same thickness. Leg and tapware prices are added separately.

Does Grade 316 apply to the support legs?

The Grade 316 option applies to the contact surfaces. Optional support legs remain Grade 304 stainless steel.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357