


PRODUCT RANGE SPECIFICATION

B34756 – Stainless Steel Wash Trough with Sensor Tap Uprand



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B34756{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

The B34756 wall-mounted stainless steel wash trough provides shared handwashing in hygiene-conscious environments, including food processing, pharmaceutical production and general manufacturing facilities.

Its wide rear upstand provides space for sensor tap electronics behind the tap mounting face. Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes. Standard bib taps can be used instead of sensor tapware.

The recommended tap is the Cobra Cobratron 04TSEN-COB-EL-1002-C wall-mounted single-temperature electronic sensor spout, supplied with a 1/2-inch solenoid valve, 9 V transformer and pressure-compensating flow restrictor. Tapware is an optional accessory, priced separately at R6,657 ex VAT per tap. Allow one tap per washing station.

The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four. Both left-hand and right-hand waste outlets are available at each length. Gallows brackets support the trough at the wall, and the sloped basin directs water towards the selected outlet.

Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units. Legs add R1,934 ex VAT per trough and supplement the wall mounting. Leg-equipped units use Grade 304 stainless steel support legs.

Standard units use 0.9 mm Grade 304 stainless steel. Advanced options are 1.2 mm thickness at 33% above the standard trough price, or 1.5 mm at a further 25% above 1.2 mm. Grade 316 contact surfaces add 50% to the selected thickness trough price. The support-leg option and tapware are added separately.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B34756 wall-mounted stainless steel wash trough with wide rear upstand for sensor tap electronics, gallows brackets and sloped basin. The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four. Left- or right-hand waste outlet. Standard 0.9 mm Grade 304; 1.2 mm, 1.5 mm and Grade 316 contact surfaces optional. Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes. Tapware priced separately. Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Rear Upstand Design	Wide rear upstand with space for sensor tap electronics	—	—
Tap Hole Provision	Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the upstand is supplied without pre-punched tap holes.	—	Tap holes are not punched as standard. Confirm the required tap or spout layout for the installation.
Mounting Type	Wall Mounted with Gallows Brackets	—	—
Tapware Supply	Optional Sensor Tapware or Standard Bib Taps; Priced Separately	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-109-1200L)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × — × — mm (L × W × H)
B34756(S-109-1200L-SL)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × — × — mm (L × W × H)
B34756(S-109-1200R)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × — × — mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-109-1200R-SL)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-109-1800L)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-109-1800L-SL)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-109-1800R)	Wall-Mounted Wash Trough with Wide Rear Upstand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-109-1800R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × × – mm (L × W × H)
B34756(S-109-2400L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × × – mm (L × W × H)
B34756(S-109-2400L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × × – mm (L × W × H)
B34756(S-109-2400R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-109-2400R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × × – mm (L × W × H)
B34756(S-112-1200L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-112-1200L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-112-1200R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-112-1200R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-112-1800L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-112-1800L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-112-1800R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-112-1800R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-112-2400L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-112-2400L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-112-2400R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-112-2400R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × × – mm (L × W × H)
B34756(S-115-1200L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-115-1200L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-115-1200R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-115-1200R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-115-1800L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-115-1800L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-115-1800R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-115-1800R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-115-2400L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-115-2400L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-115-2400R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-115-2400R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 304. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 304 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × × – mm (L × W × H)
B34756(S-309-1200L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-309-1200L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-309-1200R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-309-1200R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-309-1800L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-309-1800L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-309-1800R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-309-1800R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-309-2400L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-309-2400L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-309-2400R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-309-2400R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 0.9 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 0.9 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-312-1200L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-312-1200L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-312-1200R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-312-1200R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-312-1800L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-312-1800L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-312-1800R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-312-1800R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-312-2400L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-312-2400L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-312-2400R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-312-2400R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.2 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.2 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × × – mm (L × W × H)
B34756(S-315-1200L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-315-1200L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Left Hand Overall dimensions: 1200 × × – mm (L × W × H)
B34756(S-315-1200R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-315-1200R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1200 mm. Stations: Two. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1200 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Two Waste Outlet Orientation: Right Hand Overall dimensions: 1200 × – × – mm (L × W × H)
B34756(S-315-1800L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-315-1800L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Left Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-315-1800R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-315-1800R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 1800 mm. Stations: Three. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 1800 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Three Waste Outlet Orientation: Right Hand Overall dimensions: 1800 × – × – mm (L × W × H)
B34756(S-315-2400L)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-315-2400L-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Left Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Left Hand Overall dimensions: 2400 × – × – mm (L × W × H)
B34756(S-315-2400R)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: No. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: No Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × – × – mm (L × W × H)

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B34756(S-315-2400R-SL)	Wall-Mounted Wash Trough with Wide Rear Uprand for Sensor Tap Electronics. Length: 2400 mm. Stations: Four. Contact Surface Material: Stainless Steel Grade 316. Thickness: 1.5 mm. Waste Outlet: Right Hand. Front Support Legs Included: Yes. Gallows Brackets and Sloped Basin. Tap Holes Pre-Punched When Tapware Is Specified or Supplied. Sensor or Standard Bib Tapware Priced Separately. Leg-Equipped Units Have Grade 304 Stainless Steel Support Legs.	Front Support Legs: Yes Length: 2400 mm Material: Stainless Steel Grade 316 Material Thickness: 1.5 mm Number of Stations / Spouts: Four Waste Outlet Orientation: Right Hand Overall dimensions: 2400 × × – mm (L × W × H)

04 Functional features

01	Wide Uprand for Sensor Electronics The wide rear uprand provides space to house the electronics for sensor tapware.
02	Sensor or Standard Bib Taps Specify optional Cobra Cobratron sensor taps or use standard bib taps to suit the installation.
03	Tap Holes Matched to Specified Tapware Tap holes are pre-punched when tapware is specified or supplied with the unit; otherwise the uprand is supplied without pre-punched tap holes.
04	Two, Three or Four Washing Stations The 1200 mm trough has two washing stations, 1800 mm has three, and 2400 mm has four.
05	Optional Stainless Steel Support Legs Support legs are optional and recommended for ISO-panel mounting and for 2400 mm units. The option adds R1,934 ex VAT per trough.
06	Material Options Standard 0.9 mm Grade 304 stainless steel, with 1.2 mm and 1.5 mm thicknesses and Grade 316 contact surfaces available under advanced customisation.
07	Outlet Options and Sloped Basin Choose a left-hand or right-hand waste outlet. The sloped basin directs water towards the outlet.

05 Application information

Intended applications	Commercial Wash Troughs & Basins, General Handwashing, Hands-Free Handwashing, Pharmaceutical Support Areas
Industries	Food & Beverage Processing, General Manufacturing, Government & Public Sector, Pharmaceutical Manufacturing

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.