


PRODUCT RANGE SPECIFICATION

B35478 – Security Wash Trough



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B35478{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

Security wash trough for shared handwashing facilities in correctional and institutional environments.

The trough is 600 × 550 × 450 mm with a fully welded basin 500 × 450 × 240 mm in size. The basin features a perforated waste welded in place to protect against removal. An integral waste outlet pipe is included and can be optionally extended 250 mm out the back for connection in a duct-type installation or to the rear of the wall. The trough is supplied with a mounting frame with threaded rods for connection through the wall. This ensures that there are no connections accessible within the room and all fixations are included to the rear of the wall. The unit is manufactured from heavy-duty Stainless-Steel Grade 304 1.2 mm thick.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B35478. Security Wash Trough. The trough is 600 × 550 × 450 mm with a fully welded basin 500 × 450 × 240 mm in size. An integral waste outlet pipe is included and can be optionally extended 250 mm out the back for connection in a duct-type installation or to the rear of the wall.

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B35478	The B35478 Security Wash Trough Single Is a Robust Trough That Incorporates a High-Security, Anti-Vandal Design. The Trough Is 600x 550 x 450 mm with a Fully Welded Basin 500 x 450 x 240 mm in Size. The Basin Features a Perforated Waste Welded in Place to Protect Against Removal. An Integral Waste Outlet Pipe Is Included and Can Be Optionally Extended 250mm Out the Back for Connection in a Duct-Type Installation or to the Rear of the Wall. The Trough Is Supplied with a Mounting Frame with Threaded Rods for Connection Through the Wall. This Ensures That There Are No Connections Accessible Within the Room and All Fixations Are Included to the Rear of the Wall. The Unit Is Manufactured from Heavy-Duty Stainless-Steel Grade 304 1.2mm Thick.	Standard configuration

03 Application information

Intended applications	Commercial Wash Troughs & Basins, General Handwashing
Industries	Justice & Corrections

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.