

PRODUCT RANGE SPECIFICATION

B36640 – Stainless Steel Knee Operated Wash Hand Basin



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B36640{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

The B36640 knee-operated wash hand basin uses an Easy Push front panel that can be activated with either knee. A gooseneck spout delivers aerated water over the basin, and a stainless steel shroud encloses the plumbing.

Choose a demand tap, which flows while pressure is maintained, or a metered tap, which flows for a preset period after activation. A single-piece mounting bracket has multiple fixing holes for wall installation.

A 150 mm stainless steel splashback can be specified as an optional extra. Confirm the mounting height and access requirements for the intended users.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B36640. Stainless steel knee-operated wash basin; Easy Push front panel; aerated gooseneck spout; enclosed plumbing; single-piece mounting bracket. Demand or metered valve as selected; optional 150 mm splashback.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B36640	Knee Operated Wash Hand Basin Easy Access to Hygienic Hand Washing. A Simple Nudge with Either Your Left or Right Knee or Thigh Activates the Timed Water Flow. Standard Features: • Full Front Panel “Easy Push” Button Can Be Easily Activated with Either Left or Right Knee for Ygienic Hands Free Use. • Gooseneck Spout Provides Aerated Water for Minimum Splash • Sturdy Stainless Steel Construction Ensures Life-Long Service. • a 150mm Stainless Steel Splashback Can Be Ordered with the Unit for Easy Installation and to Comply with Plumbing Requirements of Most Authorities and Need for Tiling. • Easy Mount Single Piece Bracket Has Multiple Fixing Holes for Quick Installation by Plumber. • Stainless Steel Shroud Fully Encloses Plumbing for Additional Hygiene and Security, and Prevents Unauthorised Tampering with Plumbing Fittings. • Suitable for Use Where Disabled Access Is Required. • Two Tap Options Either demand Tap Which Requires Continuous Pressure for Water Flow or Metered Tap Which Allows Water Flow for a Predetermined Time.	Standard configuration

03 Application information

Intended applications	Change Rooms & Locker Rooms, Commercial Wash Troughs & Basins, Hands-Free Handwashing
Industries	Dairy & Beverage Processing, Fish & Seafood Processing, Food & Beverage Processing, Fresh Produce & Packhouses, Government & Public Sector, Meat & Poultry Processing

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.