

MODEL SPECIFICATION

B36645(D-112-0600C) – Knee Operated Wash Hand Basin, Grade 304 Stainless Steel 1.2mm, 600 x 435 x 692mm, Demand Valve, Rear Upstand and Bib Spout

|                |                          |                          |              |
|----------------|--------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE       | DATA STATUS              | GENERATED ON |
| Model          | B36645(D-112-0600C){PSS} | Published catalogue data | 17 Sep 2026  |

01 Technical specifications

| PARAMETER                | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                              |
|--------------------------|---------------------------|------|-----------------------------------------------------------------------------------------------------------------------------|
| Demand / Metered Valve   | Demand Valve              | —    | —                                                                                                                           |
| Material                 | Stainless Steel Grade 304 | —    | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| Waste Outlet Diameter    | 40                        | mm   | —                                                                                                                           |
| Material Thickness       | 1.2                       | mm   | The thickness of the material used for the item's primary construction. The thickness of individual components may vary.    |
| Waste Outlet Orientation | Centre                    | —    | —                                                                                                                           |
| Bowl Depth               | 150                       | mm   | —                                                                                                                           |
| Mounting Type            | Wall Mounted              | —    | —                                                                                                                           |

02 Dimensions and mass

| PARAMETER      | VALUE | UNIT |
|----------------|-------|------|
| Length         | 600   | mm   |
| Width          | 435   | mm   |
| Overall height | 692   | mm   |
| Mass           | 15.9  | kg   |

03 Model and supply data

|                   |                                                |
|-------------------|------------------------------------------------|
| Parent product    | B36645 – Knee-Operated Wash Basin with Upstand |
| Typical lead time | 10–15 working days                             |
| Warranty          | 12 months                                      |

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration description | <p>The Basterfield B36645(D-112-0600C) is a wall-mounted knee-operated wash hand basin with demand valve activation. It is manufactured from 1.2 mm Grade 304 stainless steel and measures 600 mm long x 435 mm wide x 692 mm overall height.</p> <p>The trough-style bowl is 150 mm deep, with smooth radiused corners and a central 40 mm waste outlet. An integral rear upstand helps protect the wall from splash, and a standard bib spout supplies water to the basin.</p> <p>The front-mounted control can be operated with either knee, leaving both hands free for washing. Water flows while the knee control is pressed. This is the standard demand-valve configuration.</p> |
| Short Form Specification  | <div><div>SPECIFICATION USE</div><div>Use this description when specifying this model.</div></div> <p>Basterfield B36645(D-112-0600C) knee-operated wash hand basin; Grade 304 stainless steel, 1.2 mm thick; 600 x 435 x 692 mm overall (L x W x H); 150 mm deep trough bowl with radiused corners and central 40 mm waste outlet; integral rear upstand; wall-mounted; front-mounted knee-operated demand valve; standard bib spout.</p>                                                                                                                                                                                                                                               |
| Detailed specification    | <ul style="list-style-type: none"><li>• Model: B36645(D-112-0600C)</li><li>• Material: Grade 304 stainless steel</li><li>• Material thickness: 1.2 mm</li><li>• Overall dimensions (L x W x H): 600 x 435 x 692 mm</li><li>• Bowl depth: 150 mm</li><li>• Bowl corners: Radiused</li><li>• Waste outlet: 40 mm diameter, centre</li><li>• Rear upstand: Integral</li><li>• Mounting: Wall mounted</li><li>• Valve activation: Knee-operated demand valve</li><li>• Operation: Water flows while the knee control is pressed.</li><li>• Spout: Standard bib spout</li></ul>                                                                                                               |

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.