

PRODUCT RANGE SPECIFICATION

B36645(D-312-0600C) – 600 mm
Grade 316 Knee-Operated Wash
Basin



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B36645(D-312-0600C){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

25 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/b36645d-312-0600c-600-mm-grade-316-knee-operated-wash-basin#specifications>



01 Product description and specification

Product description

600 mm Grade 316 stainless steel knee-operated wash basin with 1.2 mm construction, upstand, bib spout and demand valve.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B36645(D-312-0600C). Grade 316 stainless steel knee-operated wash basin; 1.2 mm material thickness; 600 mm length; upstand, bib spout and demand valve.

An Advanced Ø22mm thermostatic mixing valve is available as a separately priced optional extra. Choose this optional extra when hot and cold water need to be mixed into a pre-tempered supply. The knee control switches water flow on or off; it does not mix the supplies or adjust the temperature. We recommend one Advanced Ø22mm thermostatic mixing valve per single washing station.

02 Functional features

01 Optional Pre-Tempered Water

Choose this optional extra when hot and cold water need to be mixed into a pre-tempered supply. The knee control switches water flow on or off; it does not mix the supplies or adjust the temperature. We recommend one Advanced Ø22mm thermostatic mixing valve per single washing station. Valve supplied separately.

03 Application information

Intended applications

Change Rooms & Locker Rooms, Commercial Wash Troughs & Basins, Hands-Free Handwashing

Industries

Dairy & Beverage Processing, Fish & Seafood Processing, Food & Beverage Processing, Fresh Produce & Packhouses, Government & Public Sector, Meat & Poultry Processing

04 Supply and support

Typical lead time

10–15 working days

Warranty	12 months
----------	-----------

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.