

MODEL SPECIFICATION

**B36657(D) – Knee-Activated Grade 304 Stainless Steel Wash Basin with Shroud, demand Valve and Standard Splashback. Front Support Legs Are an Optional Extra; Excluded from This Base Model.**



PRODUCT IMAGE

DOCUMENT SCOPE

Model

DOCUMENT REFERENCE

B36657(D){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Technical specifications

| PARAMETER              | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                              |
|------------------------|---------------------------|------|-----------------------------------------------------------------------------------------------------------------------------|
| Demand / Metered Valve | Demand Valve              | —    | —                                                                                                                           |
| Extended Splashback    | No                        | —    | —                                                                                                                           |
| Material               | Stainless Steel Grade 304 | —    | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| Length                 | 500                       | mm   | The length of the item typically as measured from left to right.                                                            |
| Width                  | 390                       | mm   | The width of the item typically as measured from front to back.                                                             |
| Waste Outlet Diameter  | 40                        | mm   | —                                                                                                                           |
| Mounting Type          | Wall Mounted              | —    | —                                                                                                                           |
| Front Support Legs     | No                        | —    | —                                                                                                                           |

02 Dimensions and mass

| PARAMETER | VALUE | UNIT |
|-----------|-------|------|
| Length    | 500   | mm   |
| Width     | 390   | mm   |

03 Model and supply data

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Parent product    | B36657 – Knee Activated Wash Hand Basin with Shroud |
| Typical lead time | 10–15 working days                                  |
| Warranty          | 12 months                                           |

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration description | <p>The Basterfield B36657(D) is a knee-activated wash hand basin with an enclosed shroud, demand valve and standard splashback. It measures 500 mm long x 390 mm wide and has a 40 mm waste outlet and aerated gooseneck spout. Front support legs are optional and are excluded from this configuration.</p>                                                                                                                                                                                    |
| Short Form Specification  | <div><div><div>SPECIFICATION USE</div><div>Use this description when specifying this model.</div></div><p>Basterfield B36657(D). Knee-activated Grade 304 stainless steel wash basin with shroud, demand valve and standard splashback. Front support legs are an optional extra; excluded from this base model. 500 mm long x 390 mm wide; 40 mm waste outlet; aerated gooseneck spout; wall mounted. Confirm overall height and mounting details against the selected model drawing.</p></div> |
| Detailed specification    | <ul style="list-style-type: none"><li>• Model: B36657(D)</li><li>• Material: Grade 304 stainless steel</li><li>• Length: 500 mm</li><li>• Width: 390 mm</li><li>• Valve activation: Demand valve</li><li>• Splashback: standard splashback</li><li>• Waste outlet diameter: 40 mm</li><li>• Spout: Aerated gooseneck</li><li>• Mounting: Wall mounted</li><li>• Front support legs: Not included; optional extra</li></ul>                                                                       |

**Product drawings and images****PRODUCT IMAGE**

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.