MODEL SPECIFICATION

B36657(M-SL1) – Shrouded Knee Basin, Metered, Standard, Legs

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B36657(M-SL1){PSS}	15 Nov 2026

01 Model specification

Knee-Activated Grade 304 Stainless Steel Wash Basin with Shroud, Metered Valve and Standard Splashback. Includes Optional Front Support Legs with Adjustable Feet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Extended Splashback	No	–	–
Demand / Metered Valve	Metered Valve	–	–
Front Support Legs	Yes	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Width	390	mm	The width of the item typically as measured from front to back.
Waste Outlet Diameter	40	mm	–
Mounting Type	Wall Mounted	–	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	500	mm
Width	390	mm

04 Model and supply data

Parent product	B36657 – Knee Activated Wash Hand Basin with Shroud
Typical lead time	10–15 working days
Warranty	12 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

05 Specification notes

Configuration description	The Basterfield B36657M-SL1 is a knee-activated wash hand basin with an enclosed shroud, metered valve and standard splashback. It measures 500 mm long x 390 mm wide and has a 40 mm waste outlet and aerated gooseneck spout. This configuration includes the optional 25 x 25 mm Grade 304 square tubular front support legs with adjustable feet. Price on request.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this model. Basterfield B36657M-SL1. Knee-activated Grade 304 stainless steel wash basin with shroud, metered valve and standard splashback. Includes optional front support legs with adjustable feet. 500 mm long x 390 mm wide; 40 mm waste outlet; aerated gooseneck spout; wall mounted. Confirm overall height and mounting details against the selected model drawing.
Detailed specification	• Model: B36657M-SL1 • Material: Grade 304 stainless steel • Length: 500 mm • Width: 390 mm • Valve activation: Metered valve • Splashback: standard splashback • Waste outlet diameter: 40 mm • Spout: Aerated gooseneck • Mounting: Wall mounted • Front support legs: Included as optional extra • Leg section: 25 x 25 mm square tube • Leg material: Grade 304 stainless steel • Feet: Adjustable

06 Frequently asked questions

What is the difference between B36657(D) and B36657(DE)?

Both use a demand valve. B36657(D) has the standard splashback, while B36657(DE) has a 400 mm extended splashback.

Are front support legs included in the displayed base prices?

No. Front support legs are an optional extra. The B36657(D) and B36657(DE) base prices exclude legs. Select Yes under Optional front support legs for a leg-equipped configuration and request its price.

What are the optional legs made from?

The legs use 25 x 25 mm square tubular Grade 304 stainless steel with adjustable feet for levelling.

How do demand and metered valves differ?

A demand valve supplies water while the knee panel is pressed. A metered valve supplies water for a preset period after activation. Metered configurations are available under Show advanced options.

What dimensions and waste connection are specified?

The basin is 500 mm long x 390 mm wide and has a 40 mm waste outlet. The extended splashback is 400 mm high. Confirm overall height, fixing positions and installation clearances against the selected model drawing.

How is the basin installed?

The basin is wall mounted using a mounting bracket. Coordinate suitable wall support, mounting height, water supply and waste plumbing with the installer.

Where can this basin be used?

Typical uses include staff handwashing points in food processing facilities, commercial kitchens, change rooms and institutional washrooms. Match the configuration to the site requirements.

Do catalogue prices include VAT?

Displayed catalogue prices exclude VAT. Front support legs are optional and are excluded from the B36657(D) and B36657(DE) base prices. Metered and leg-equipped configurations are priced on request.

When should I select the optional thermostatic mixing valve?

Choose this optional extra when hot and cold water need to be mixed into a pre-tempered supply. The knee control switches water flow on or off; it does not mix the supplies or adjust the temperature. The Advanced Ø22mm valve is supplied and priced separately from the basin.

How many thermostatic mixing valves are recommended?

We recommend one Advanced Ø22mm thermostatic mixing valve per single washing station. Select the valve separately when requesting a quotation.

Does knee operation adjust the water temperature?

No. Knee operation controls the water flow only. A demand valve flows while pressed; a metered valve supplies a preset flow period after activation, where that option is available. For mixed warm water, a thermostatic mixing valve blends the hot and cold supplies upstream. A site that already supplies suitably pre-tempered water may not need an additional local mixing valve.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357