

MODEL SPECIFICATION

B36657(M-SL1) – Knee-activated Grade 304 stainless steel wash basin with shroud, metered valve and standard splashback. Includes optional front support legs with adjustable feet.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B36657(M-SL1){PSS}	Published catalogue data	20 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Extended Splashback	No	—	—
Demand / Metered Valve	Metered Valve	—	—
Front Support Legs	Yes	—	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Width	390	mm	The width of the item typically as measured from front to back.
Waste Outlet Diameter	40	mm	—
Mounting Type	Wall Mounted	—	—

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	500	mm
Width	390	mm

03 Model and supply data

Parent product	B36657 – Knee Activated Wash Hand Basin with Shroud
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	The Basterfield B36657M-SL1 is a knee-activated wash hand basin with an enclosed shroud, metered valve and standard splashback. It measures 500 mm long x 390 mm wide and has a 40 mm waste outlet and aerated gooseneck spout. This configuration includes the optional 25 x 25 mm Grade 304 square tubular front support legs with adjustable feet. Price on request.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B36657M-SL1. Knee-activated Grade 304 stainless steel wash basin with shroud, metered valve and standard splashback. Includes optional front support legs with adjustable feet. 500 mm long x 390 mm wide; 40 mm waste outlet; aerated gooseneck spout; wall mounted. Confirm overall height and mounting details against the selected model drawing.
Detailed specification	• Model: B36657M-SL1 • Material: Grade 304 stainless steel • Length: 500 mm • Width: 390 mm • Valve activation: Metered valve • Splashback: standard splashback • Waste outlet diameter: 40 mm • Spout: Aerated gooseneck • Mounting: Wall mounted • Front support legs: Included as optional extra • Leg section: 25 x 25 mm square tube • Leg material: Grade 304 stainless steel • Feet: Adjustable

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.