MODEL SPECIFICATION

B36657(DE) – Shrouded Knee Basin, Demand, Extended

PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B36657(DE){PSS}	Published catalogue data	25 Oct 2026

01 Model specification

Knee-Activated Grade 304 Stainless Steel Wash Basin with Shroud, demand Valve and 400 mm Extended Splashback. Front Support Legs Are an Optional Extra; Excluded from This Base Model.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Demand / Metered Valve	Demand Valve	–	–
Extended Splashback	Yes	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Width	390	mm	The width of the item typically as measured from front to back.
Waste Outlet Diameter	40	mm	–
Mounting Type	Wall Mounted	–	–
Splashback Height	400	mm	Height of the splashback above the tabletop or working surface.
Front Support Legs	No	–	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	500	mm

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Width	390	mm

04 Model and supply data

Parent product	B36657 — Knee Activated Wash Hand Basin with Shroud
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

The Basterfield B36657(DE) is a knee-activated wash hand basin with an enclosed shroud, demand valve and 400 mm extended splashback. It measures 500 mm long x 390 mm wide and has a 40 mm waste outlet and aerated gooseneck spout. Front support legs are optional and are excluded from this configuration.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B36657(DE). Knee-activated Grade 304 stainless steel wash basin with shroud, demand valve and 400 mm extended splashback. Front support legs are an optional extra; excluded from this base model. 500 mm long x 390 mm wide; 40 mm waste outlet; aerated gooseneck spout; wall mounted. Confirm overall height and mounting details against the selected model drawing.

Detailed specification

- Model: B36657(DE)
- Material: Grade 304 stainless steel
- Length: 500 mm
- Width: 390 mm
- Valve activation: Demand valve
- Splashback: 400 mm extended splashback
- Waste outlet diameter: 40 mm
- Spout: Aerated gooseneck
- Mounting: Wall mounted
- Front support legs: Not included; optional extra

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.