PRODUCT RANGE SPECIFICATION

B36657 – Knee Activated Wash Hand Basin with Shroud



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B36657{PSS}	15 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b36657-knee-activated-wash-hand-basin-with-shroud#specifications

01 Product description and specification

Product description

Knee-activated Grade 304 stainless steel wash hand basin with an enclosed shroud and aerated gooseneck spout. Choose a standard or 400 mm extended splashback. Demand valve operation is standard; metered valve models are available under advanced options. Front support legs are an optional extra and are excluded from the base-model prices.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B36657 knee-activated wash hand basin with enclosed shroud. Grade 304 stainless steel; 500 mm long x 390 mm wide; 40 mm waste outlet; aerated gooseneck spout; wall mounted. Standard or 400 mm extended splashback. Demand valve standard; metered valve under advanced options. Front support legs are an optional extra, excluded from base-model prices. Confirm overall height and mounting details against the selected model drawing.

An Advanced Ø22mm thermostatic mixing valve is available as a separately priced optional extra. Choose this optional extra when hot and cold water need to be mixed into a pre-tempered supply. The knee control switches water flow on or off; it does not mix the supplies or adjust the temperature. We recommend one Advanced Ø22mm thermostatic mixing valve per single washing station.

02 Configuration options

Extended splashback (400 mm)	No; Yes
Optional front support legs	No; Yes

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 **Knee-operated front panel**
Operate the valve with either knee to leave both hands free for washing.

02 **Enclosed stainless steel shroud**
The shroud encloses the basin plumbing.

03 **Grade 304 stainless steel**
Grade 304 stainless steel basin construction.

04 **Aerated gooseneck spout**
A gooseneck outlet provides an aerated water stream.

05 **Choice of splashback**
Choose the standard splashback or the 400 mm extended splashback.

06 **Optional front support legs**
25 x 25 mm Grade 304 square tubular legs with adjustable feet are available as an optional extra; base prices exclude legs.

07 **Optional Pre-Tempered Water**
Choose this optional extra when hot and cold water need to be mixed into a pre-tempered supply. The knee control switches water flow on or off; it does not mix the supplies or adjust the temperature. We recommend one Advanced Ø22mm thermostatic mixing valve per single washing station. Valve supplied separately.

04 Application information

Intended applications	Change Rooms & Locker Rooms, Commercial Wash Troughs & Basins, Hands-Free Handwashing
Industries	Cannabis, Dairy & Beverage Processing, Fish & Seafood Processing, Food & Beverage Processing, Fresh Produce & Packhouses, Government & Public Sector, Meat & Poultry Processing

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

What is the difference between B36657(D) and B36657(DE)?
Both use a demand valve. B36657(D) has the standard splashback, while B36657(DE) has a 400 mm extended splashback.

Are front support legs included in the displayed base prices?
No. Front support legs are an optional extra. The B36657(D) and B36657(DE) base prices exclude legs. Select Yes under Optional front support legs for a leg-equipped configuration and request its price.

What are the optional legs made from?
The legs use 25 x 25 mm square tubular Grade 304 stainless steel with adjustable feet for levelling.

How do demand and metered valves differ?
A demand valve supplies water while the knee panel is pressed. A metered valve supplies water for a preset period after activation. Metered configurations are available under Show advanced options.

What dimensions and waste connection are specified?
The basin is 500 mm long x 390 mm wide and has a 40 mm waste outlet. The extended splashback is 400 mm high. Confirm overall height, fixing positions and installation clearances against the selected model drawing.

How is the basin installed?
The basin is wall mounted using a mounting bracket. Coordinate suitable wall support, mounting height, water supply and waste plumbing with the installer.

Where can this basin be used?

Typical uses include staff handwashing points in food processing facilities, commercial kitchens, change rooms and institutional washrooms. Match the configuration to the site requirements.

Do catalogue prices include VAT?

Displayed catalogue prices exclude VAT. Front support legs are optional and are excluded from the B36657(D) and B36657(DE) base prices. Metered and leg-equipped configurations are priced on request.

When should I select the optional thermostatic mixing valve?

Choose this optional extra when hot and cold water need to be mixed into a pre-tempered supply. The knee control switches water flow on or off; it does not mix the supplies or adjust the temperature. The Advanced Ø22mm valve is supplied and priced separately from the basin.

How many thermostatic mixing valves are recommended?

We recommend one Advanced Ø22mm thermostatic mixing valve per single washing station. Select the valve separately when requesting a quotation.

Does knee operation adjust the water temperature?

No. Knee operation controls the water flow only. A demand valve flows while pressed; a metered valve supplies a preset flow period after activation, where that option is available. For mixed warm water, a thermostatic mixing valve blends the hot and cold supplies upstream. A site that already supplies suitably pre-tempered water may not need an additional local mixing valve.

Product drawings and images



PRODUCT IMAGE



PRODUCT IMAGE

E&OE. Specifications are subject to change without notice.