MODEL SPECIFICATION

B36658(M) – Wash Basin, Knee Operated, Metered Valve

PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B36658(M){PSS}	Published catalogue data	25 Oct 2026

01 Model specification

Wash Basin, Grade 304 Stainless Steel, 0.9mm Main Construction, with 50mm Standard Splashback, Ø40mm Pre-Punched Waste Outlet, 15mm Water Inlet, Easy Push Knee-Operated Front Panel, Metered Valve Activation, Aerated Gooseneck Spout and Specification Reference B36658{PSS}

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Extended Splashback	No	–	–
Demand / Metered Tap	Metered Tap	–	Demand Tap (standard): water flows while the knee panel is pressed and stops when released. Metered Tap: one press starts water flow for a preset period, then it stops automatically.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	Thickness of the main construction. Individual components may differ.
Waste Outlet Diameter	40	mm	Pre-punched waste outlet in the basin.
Inlet Diameter	15	mm	Water inlet connection size.
Splashback Height	50	mm	Height of the splashback above the tabletop or working surface.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

03 Model and supply data

Parent product	B36658 — Stainless Steel Knee Activated Wash Hand Basin
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The Basterfield B36658(M) is a Grade 304 stainless steel knee-operated wash hand basin with 0.9mm main construction and metered valve activation. Its Easy Push front panel can be operated with either knee. Water flows for a preset period after the knee panel is activated.

Supplied with a 50mm standard splashback, aerated gooseneck spout and easy-mount wall bracket with multiple fixing holes. The basin has a pre-punched 40mm waste outlet and a 15mm water inlet.

This metered model is available under advanced customisation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B36658(M) wall-mounted knee-operated wash hand basin in Grade 304 stainless steel with 0.9mm main construction; Easy Push front panel; metered valve activation; aerated gooseneck spout; mounting bracket with multiple fixing holes; 50mm standard splashback; pre-punched 40mm waste outlet; 15mm water inlet. Thermostatic mixing valve optional and supplied separately.

Detailed specification

- Model: B36658(M)
- Specification reference: B36658{PSS}
- Material: Grade 304 stainless steel
- Main construction thickness: 0.9mm
- Activation: Easy Push knee-operated front panel
- Valve: Metered
- Operation: Water flows for a preset period after the knee panel is activated.
- Spout: Aerated gooseneck
- Mounting: Wall bracket with multiple fixing holes
- Splashback: 50mm standard splashback
- Waste outlet: Pre-punched 40mm outlet
- Water inlet: 15mm
- Thermostatic mixing valve: Optional, supplied separately

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.