

MODEL SPECIFICATION

B36658(DE) – Knee Operated Wash Basin with Extended Splashback and Demand Valve Activation to B36658{PSS}



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
B36658(DE){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT
Extended Splashback	Yes	—
Demand / Metered Tap	Demand Tap	—

02 Model and supply data

Parent product	B36658 – Stainless Steel Knee Activated Wash Hand Basin
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	The Basterfield B36658(DE) is a stainless steel knee-operated wash hand basin with demand valve activation. Its Easy Push front panel can be operated with either knee. Water flows while the knee panel is pressed. Includes the extended stainless steel splashback. The basin has an aerated gooseneck spout and an easy-mount wall bracket with multiple fixing holes.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B36658(DE) knee-operated wash hand basin to B36658{PSS}; stainless steel construction; Easy Push front panel; demand valve activation; aerated gooseneck spout; wall mounting bracket with multiple fixing holes; extended stainless steel splashback included.
Detailed specification	• Model: B36658(DE) • Specification reference: B36658{PSS} • Material: Stainless steel • Activation: Easy Push knee-operated front panel • Valve: Demand • Operation: Water flows while the knee panel is pressed. • Spout: Aerated gooseneck • Mounting: Wall bracket with multiple fixing holes • Extended splashback: Yes

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.