MODEL SPECIFICATION

# B36661(S-G1-SL) – Wash Hand Basin with Front Support Legs



PRODUCT IMAGE

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | B36661(S-G1-SL){PSS} | 18 Nov 2026 |

## 01 Model specification

Wash Hand Basin, Grade 304 Stainless Steel, 1.2mm Thick, 500mm (L) × 420mm (W), with 440mm (L) × 310mm (W) × 150mm (D) Bowl, 25mm Radiused Bowl Corners, 50mm Rear Splashback, 26mm Turndown Edge, Ø40mm Waste Outlet Hole, and 25mm × 25mm Square Tubular Stainless Steel Gallows Brackets with 215mm Vertical Mounting-Hole Pitch, with Front Support Legs and Adjustable Feet. Basin and Bracket Assembly Height Is 400mm; Installed Height Is Set to Suit the Installation. Tapware, Tap-Hole Arrangement, Waste Fitting, Trap and Pipework to Be Specified

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Front Support Legs** | Yes | – | – |
| **Mounting Type** | Stainless Steel Gallows Brackets | – | – |
| **Material** | Stainless Steel Grade 304 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| **Waste Outlet Diameter** | 40 | mm | – |
| **Material Thickness** | 1.2 | mm | The thickness of the material used for the item's primary construction. The thickness of individual components may vary. |
| **Splashback Height** | 50 | mm | Height of the splashback above the tabletop or working surface. |
| **Bowl Length** | 440 | mm | The length of the bowl typically as measured from left to right. |
| **Bowl Width** | 310 | mm | – |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Bowl Depth** | 150 | mm | — |
| **Length** | 500 | mm | The length of the item typically as measured from left to right. |
| **Width** | 420 | mm | The width of the item typically as measured from front to back. |
| **Number of Bowls** | 1 | — | — |
| **Basin and Bracket Height** | 400 | mm | Vertical dimension from the top of the splashback to the bottom of the wall-mounting brackets. The installed height above the floor is set during installation. |
| **Turndown Edge** | 26 | mm | — |
| **Bracket Tube Section** | 25 × 25mm square stainless steel tube | — | — |
| **Bracket Mounting Hole Pitch** | 215 | mm | Vertical centre-to-centre spacing of the mounting holes on each wall bracket. |
| **Bowl Corner Radius** | 25 | mm | — |
| **Waste Outlet Hole** | Ø40mm outlet hole | — | — |
| **Tap Hole Provision** | Tap-hole arrangement to be specified | — | Specify the tap-hole arrangement to suit the selected tapware. |
| **Tapware Supply** | Tapware to be specified separately | — | — |

## 03 Model and supply data

| | |
|---|---|
| **Parent product** | B36661(S) — Wash Hand Basin with Radiused Corners |
| **Typical lead time** | 10–15 working days |
| **Warranty** | 12 months |

## 04 Specification notes

**Configuration description**

The B36661(S-G1-SL) wash hand basin is suitable for medical and healthcare handwashing areas. Its 25 mm radiused internal bowl corners form curved junctions that are easier to reach during routine cleaning. It also suits general handwashing in laboratories, food-processing facilities, catering areas and institutional buildings.

Both configurations use 1.2 mm Grade 304 stainless steel and share a 500 mm x 420 mm basin with a 440 mm x 310 mm x 150 mm deep bowl. An integrated 50 mm rear splashback helps protect the wall. The basin has a 26 mm turndown edge and a 40 mm waste outlet hole.

This configuration includes stainless steel gallows brackets and stainless steel front support legs with adjustable feet.

The wall-mount assembly measures 400 mm from the top of the splashback to the bottom of the brackets. This is separate from the installed height above the floor. Specify the tapware, tap-hole arrangement, waste fitting, trap and plumbing connections for the installation.

**Short Form Specification**

**SPECIFICATION USE**
Use this description when specifying this model.

Basterfield B36661(S-G1-SL) wash hand basin in 1.2 mm Grade 304 stainless steel, 500 mm (L) x 420 mm (W), with a 440 mm (L) x 310 mm (W) x 150 mm (D) bowl, 50 mm rear splashback and 26 mm turndown edge. 25 mm radiused internal bowl corners and 40 mm waste outlet hole. Include 25 x 25 mm square tubular stainless steel gallows brackets with a 215 mm vertical mounting-hole pitch. Basin and bracket assembly height 400 mm; installed height to suit the installation. This configuration includes stainless steel gallows brackets and stainless steel front support legs with adjustable feet. Tapware, tap-hole arrangement, waste fitting, trap and pipework to be specified.

**Detailed specification**

- Model: B36661(S-G1-SL)
- Material: Stainless Steel Grade 304
- Material Thickness: 1.2 mm
- Basin Dimensions: 500 mm (L) x 420 mm (W)
- Number of Bowls: 1
- Bowl Dimensions: 440 mm (L) x 310 mm (W) x 150 mm (D)
- Splashback Height: 50 mm
- Turndown Edge: 26 mm
- Mounting: Stainless steel gallows brackets
- Bracket Tube: 25 x 25 mm square stainless steel
- Bracket Mounting-Hole Pitch: 215 mm vertically
- Basin and Bracket Assembly Height: 400 mm; height above the floor set during installation
- Front Support Legs: Included, with adjustable feet
- Bowl Corner Radius: 25 mm
- Waste Outlet Hole: 40 mm
- Tapware, tap-hole arrangement, waste fitting, trap and connecting pipework: Specify with quotation

## 05 Frequently asked questions

**Why is this basin suitable for medical handwashing areas?**

The 25 mm radiused internal bowl corners form curved junctions that are easier to reach during routine cleaning. The basin is suitable for medical and healthcare handwashing, with tapware selected for the intended task.

**What material and thickness are used?**

Both configurations use 1.2 mm Grade 304 stainless steel.

**What are the basin and bowl dimensions?**

The basin measures 500 mm long x 420 mm wide, with a 440 mm long x 310 mm wide x 150 mm deep bowl. The 400 mm height on the wall-mount drawing includes the splashback and brackets; it is not the installed height above the floor.

**What is the difference between S-G1 and S-G1-SL?**

B36661(S-G1) includes stainless steel gallows brackets without front support legs. B36661(S-G1-SL) adds stainless steel front support legs with adjustable feet. Both use the same radiused-corner basin.

**What splashback and edge details are provided?**

The basin has a 50 mm integrated rear splashback and a 26 mm turndown edge.

**How is the basin supported?**

The included gallows brackets use 25 x 25 mm square stainless steel tube with mounting holes at a 215 mm vertical pitch. The SL configuration also includes front support legs with adjustable feet. Set the basin mounting height to suit the installation.

**What tapware and waste details should be specified?**

The basin has a 40 mm waste outlet hole. Specify the tapware, tap-hole arrangement, waste fitting, trap and connecting pipework with the quotation.

**Can the basin be used outside medical facilities?**

Yes. It also suits general handwashing in laboratories, food-processing facilities, catering areas and institutional buildings. Select the support arrangement and tapware for the intended setting.

E&OE. Specifications are subject to change without notice.


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357