

MODEL SPECIFICATION

B37355(DC-115-2250-E0500) – Complete 2250 mm double-centre utensil wash sink in 1.5 mm grade 304 stainless steel with an integral 500 mm high extended splashback. Two 1000 x 990 x 500 mm bowls and 90 mm waste outlets.

DOCUMENT SCOPE Model	DOCUMENT REFERENCE B37355(DC-115-2250-E0500){PSS}	DATA STATUS Published catalogue data	GENERATED ON 15 Sep 2026
-------------------------	--	---	-----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Splashback Height	500	mm	The height of the raised section designed to prevent water or debris from reaching the surrounding wall.

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	2250	mm

03 Model and supply data

Parent product	B37355(DC-E) – 2250 mm Double-Bowl Utensil Wash Sink with Integral Splashback
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description	Complete 2250 mm utensil wash sink with an integral 500 mm high extended splashback. The sink and splashback form one complete assembly. Manufactured in 1.5 mm grade 304 stainless steel with two centre bowls, each measuring 1000 x 990 x 500 mm, and 90 mm waste outlets. Compatible with pre-rinse spray units.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Complete 2250 mm double-centre utensil sink; 1.5 mm grade 304 stainless steel; integral 500 mm splashback; two 1000 x 990 x 500 mm bowls; 90 mm waste outlets.

Detailed specification

- Model: B37355(DC-115-2250-E0500)
- Overall sink length: 2250 mm
- Splashback: Integral extended splashback, 500 mm high
- Supply: Complete utensil wash sink
- Construction: 1.5 mm grade 304 stainless steel
- Bowl configuration: Double centre bowl
- Bowl dimensions, each: 1000 mm (L) x 990 mm (W) x 500 mm (H)
- Waste outlets: 90 mm
- Compatible with pre-rinse spray units

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.