PRODUCT RANGE SPECIFICATION

B37356 – Scullery Wash Trough



PRODUCT IMAGE · 1700mm x 750mm variant shown. Choose the required length and width.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	**B37356{PSS}**	**Published catalogue data**	**1 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b37356-scullery-wash-trough#specifications

01 Product description and specification

Product description

Grade 304 stainless steel scullery wash trough for soaking and rinsing crates, trays and utensils. Available in 1600mm or 1700mm lengths and 650mm, 700mm or 750mm widths, with a 400mm bowl depth, sloping front, cross-braced framework and 150mm rear splashback.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B37356 Scullery Wash Trough with 1.2mm Grade 304 stainless steel body, sloping front face, 400mm bowl depth and 25mm radiused corners. Lengths: 1600mm or 1700mm. Widths: 650mm standard, 700mm or 750mm. Working height: 900mm; overall height: 1050mm including 150mm rear splashback. Grade 304 stainless steel 40 × 40mm tubular framework with cross bracing, stainless steel adjustable feet and standard Ø90mm waste outlet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	900mm to the working rim, excluding the 150mm rear splashback.
Splashback Height	150	mm	150mm rear splashback above the 900mm working rim, giving a 1050mm overall height.
Overall height	1050	mm	Overall height of 1050mm, including the 150mm rear splashback.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The trough body is manufactured from Grade 304 stainless steel.
Material Thickness	1.2	mm	1.2mm thickness of the Grade 304 stainless steel trough body.
Bowl Depth	400	mm	400mm bowl depth across all length and width variants.
Adjustable Feet	Yes	–	–
Cross Bracing	Yes	–	Cross bracing supports the stainless steel tubular framework of the wash trough.
Number of Bowls	1	–	–
Mounting Type	Stainless Steel Tubular Stand	–	–
Bowl Corner Radius	25	mm	25mm radiused bowl corners make the internal corners easier to reach and clean.
Waste Outlet Diameter	90	mm	Standard Ø90mm waste outlet. Coordinate the waste fitting and downstream drainage connection for the installation.
Framework Material	Stainless Steel Grade 304	–	The tubular framework is manufactured from Grade 304 stainless steel.
Framework Profile	40 × 40mm Square Tubular Framework	–	40mm x 40mm square stainless steel tubular framework, with cross bracing to support the wash trough.
Feet Material	Stainless Steel	–	Stainless steel adjustable feet allow levelling during installation.
Face Style	Sloping Front Face	–	Sloping front face of the scullery wash trough.
Splashback Configuration	Rear Splashback	–	–

03 Configuration options

Length	1600 mm; 1700 mm
Width	650 mm; 700 mm; 750 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **400mm Deep Wash Bowl**

A 400mm bowl depth provides space for manual soaking and rinsing of crates, trays, utensils and removable equipment. Check the usable internal clearances against the articles being washed.

02 **1.2mm Grade 304 Stainless Steel Body**

The trough body is manufactured from 1.2mm Grade 304 stainless steel for routine washing in commercial sculleries and food production areas.

03 **25mm Radiused Corners**

Rounded bowl corners make the internal corners easier to reach and clean during routine hygiene procedures.

04 **Sloping Front Face**

A sloping front face gives the trough its angled profile for manual washing and rinsing tasks.

05 **Cross-Braced Stainless Steel Framework**

The 40 × 40mm Grade 304 stainless steel tubular framework includes cross bracing to support the trough.

06 **Stainless Steel Adjustable Feet**

Adjustable stainless steel feet allow the trough to be levelled during installation.

07 **150mm Rear Splashback**

The rear splashback helps contain splashes behind the wash area. The working height is 900mm, with an overall height of 1050mm including the splashback.

08 **Standard Ø90mm Waste Outlet**

A Ø90mm waste outlet is provided as standard. Coordinate the waste fitting and drainage connection with the installation requirements.

09 **Choice of Length and Width**

Choose 1600mm or 1700mm length. The standard width is 650mm, with 700mm and 750mm width variants available to suit the wash area.

05 Application information

Intended applications	Hygienic Wash-Down & Cleaning, Kitchen Washing & Warewashing, Utensil & Tray Washing
Industries	Food & Beverage Processing, Hospitality & Foodservice, Institutional & Contract Catering

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

What is the scullery wash trough used for?

Manual soaking and rinsing of crates, trays, utensils and removable equipment in food production facilities, commercial sculleries and catering wash-up areas.

Which lengths and widths are available?

Choose 1600mm or 1700mm length, each available in 650mm, 700mm or 750mm width. The standard width is 650mm; 700mm and 750mm are wider variants.

How deep is the bowl?

The bowl depth is 400mm across all six variants. Overall length and width describe the outside dimensions; confirm the usable internal dimensions for your crates and equipment.

Does the 900mm height include the splashback?

No. The working height is 900mm. The 150mm rear splashback brings the overall height to 1050mm.

What materials are used?

The body is 1.2mm Grade 304 stainless steel. The 40 × 40mm tubular framework is also Grade 304 stainless steel and includes cross bracing. The adjustable feet are stainless steel.

What supports routine cleaning?

The bowl has 25mm radiused corners for easier access during cleaning, together with a stainless steel body and a rear splashback to help contain splashes.

What waste outlet is provided?

A Ø90mm waste outlet is standard. Confirm the required waste fitting, closure for soaking and downstream drainage connection when specifying the installation.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357