MODEL SPECIFICATION

B38135(P12) – Wall Mounted Boot Rack - 12 Pairs



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B38135(P12){PSS}	14 Nov 2026

01 Model specification

Wall Mounted Grade 304 Stainless Steel Boot Rack for 12 Boot Pairs. 1050 mm (L) x 396 mm (W) x 924 mm (H); Square Tubular Prongs and Integral Mounting Brackets.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Boot Pairs	12	–	The number of pairs of boots that can be stored/hung on the unit.
Length	1050	mm	The length of the item typically as measured from left to right.
Width	396	mm	The width of the item typically as measured from front to back.
Height	924	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	–	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1050	mm

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Width	396	mm
Overall height	924	mm

04 Model and supply data

Parent product	B38135 — Wall-Mounted Stainless Steel Boot Rack with Square Prongs
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

The Basterfield B38135(P12) provides wall mounted storage for 12 boot pairs. The rack is manufactured from Grade 304 stainless steel with individual square tubular boot-support prongs and integral mounting brackets.

Overall dimensions are 1050 mm length x 396 mm width x 924 mm height. The stated height is the rack height, separate from its installation position above the floor.

Use it in changing rooms, locker rooms and footwear or PPE storage areas where wellington or work boots need to be organised. Select suitable wall support and fixings for the loaded rack, with access for placing and removing boots and cleaning around the installation.

The open layout allows air circulation around stored footwear. Follow the workplace cleaning and maintenance procedure for the stainless steel rack and its mounting fixings.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

Basterfield B38135(P12) wall mounted boot rack for 12 boot pairs, Grade 304 stainless steel with individual square tubular prongs and integral mounting brackets. Overall dimensions 1050 mm (L) x 396 mm (W) x 924 mm (H). Provide suitable wall support, fixings and access clearances.

Detailed specification

Specification	Detail
Model	B38135(P12)
Boot-pair capacity	12 pairs
Overall length	1050 mm
Overall width	396 mm
Overall height	924 mm
Material	Stainless Steel Grade 304
Prongs	Individual square tubular boot-support prongs
Mounting	Wall mounted with integral mounting brackets
Installation	Confirm supporting wall, fixings, access and cleaning clearance

06 Frequently asked questions

How many pairs of boots can the rack accommodate?

The range offers 8, 12, 16, 20, 24 and 36 boot pairs. A pair means two boots; choose the required model by its stated pair capacity.

How are the boots stored on the rack?

Each pair of boots is stored inverted on individual stainless steel tubular boot pegs. This keeps the boots separated, allows them to drain and air more freely, and keeps footwear off floors and other surfaces.

What are the model dimensions?

All models are 396 mm wide. P08 and P12: 1050 mm long x 924 mm high. P16: 1050 x 1134 mm. P20: 1310 x 1134 mm. P24: 1050 x 1590 mm. P36: 1570 x 1590 mm. Length is listed before height in each case.

Why do the 8- and 12-pair options have the same overall dimensions?

The supplied specification lists both B38135(P08) and B38135(P12) at 1050 x 396 x 924 mm overall, with capacities of 8 and 12 boot pairs respectively. Select by the stated capacity as well as the available installation space.

What is the rack made from?

The B38135 range is specified in Grade 304 stainless steel with individual square tubular boot-support prongs and integral wall mounting brackets.

How is the rack installed?

Fix it to a suitable load-bearing wall or support structure. Confirm fixings for the substrate and loaded rack, and allow space to place and remove boots and clean around the installation.

Does the stated height include the mounting height above the floor?

No. The listed height is the overall height of the rack itself. Set its position above the floor to suit access, the boots being stored and site cleaning requirements.

Where can this boot rack be used?

Use it in changing rooms, locker rooms and footwear storage areas in food processing, agriculture, laundries, manufacturing, mining and construction, or in healthcare, laboratory, pharmaceutical, veterinary and catering areas where work boots are worn.

What does the rack provide for drying?

The open prong layout allows air circulation around stored boots. No powered drying equipment or drying-time performance is specified for this rack.

How should it be maintained?

Clean the rack with products and methods suitable for Grade 304 stainless steel and follow the workplace cleaning procedure. Inspect the prongs, brackets and wall fixings regularly.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357