MODEL SPECIFICATION

B52672(0600G) – Sanitation Bath, Footwear, 1 Walkway

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B52672(0600G){PSS}	18 Nov 2026

01 Model specification

Footwear Sanitation Bath, Grade 304 Stainless Steel, 650mm (L) x 600mm (W) x 190mm (H), with Floor Mounting, 1 Walkway, No Handrails and Removable Grade 304 Stainless Steel Grid Insert

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Width	600	mm	The width of the item typically as measured from front to back.
Length	650	mm	The length of the item typically as measured from left to right.
Number of Walkways	1	–	–
Safety Handrails	No	–	–
Removable Insert	Grade 304 Stainless Steel Grid	–	Removable walking surface fitted to the footwear sanitation bath.
Bath Height	190	mm	Vertical height of the sanitation bath body. Safety handrail height is separate.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	650	mm
Width	600	mm
Overall height	190	mm

04 Model and supply data

Parent product	B52672 – Footwear Sanitation Baths without Handrails
Typical lead time	10–15 working days
Warranty	12 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

05 Specification notes

Configuration description	Floor-mounted footwear sanitation bath with Grade 304 stainless steel main construction. Bath dimensions: 650mm (L) x 600mm (W) x 190mm (H). The 600mm width provides 1 walkway. Supplied without handrails. The removable grid insert is Grade 304 stainless steel.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this model. Floor Mounted Footwear Sanitation Bath, 1 Walkway, 650mm (L) x 600mm (W) x 190mm (H), Grade 304 Stainless Steel Construction, without Handrails, with Removable Grade 304 Stainless Steel Grid Insert.
Detailed specification	Model: B52672(0600G) Main Construction: Grade 304 Stainless Steel Bath Dimensions: 650mm (L) x 600mm (W) x 190mm (H) Number of Walkways: 1 Safety Handrails: No Insert: Removable Grade 304 Stainless Steel Grid Insert

06 Frequently asked questions

What is the B52672 range used for?

B52672 baths provide a defined footwear sanitation point at work-area entrances and transitions into production areas, as part of the site footwear hygiene procedure. Applications include food and beverage facilities, meat and poultry processing areas, and changing-room exits leading into production.

What is the difference between B52672 and B52673?

B52672 is supplied without safety handrails. B52673 is the corresponding range with safety handrails. Both ranges offer removable aluminium treadplate or Grade 304 stainless steel grid inserts.

Which removable inserts can I choose?

Choose removable aluminium treadplate inserts or a removable Grade 304 stainless steel grid insert. The listed single-walkway models are B52672(0600) with aluminium treadplate and B52672(0600G) with a stainless steel grid.

What material is used for the bath construction?

The main construction is Grade 304 stainless steel. The treadplate inserts are aluminium, while the stainless steel grid option is also Grade 304.

Which walkway widths are available?

The range is available in one, two and three walkway widths. The two listed models are the single-walkway versions. Contact Basterfield for the wider configurations and their model-specific dimensions and pricing.

What are the overall dimensions of B52672(0600)?

Overall outside dimensions are 689mm (L) x 602mm (W) x 187mm (H). The overall length includes the feet projection; the bath-body length is 642mm. Use the outside dimensions when planning the installation space. Overall height varies with foot adjustment.

How are the inserts, feet and drainage arranged on B52672(0600)?

The aluminium model has two removable treadplate panels with lifting holes, four screw-adjustable feet for levelling and a low-level side drain outlet for solution changes and cleaning. The outlet centre is 49mm above the floor at the stated overall height.

How do I access the bath interior for cleaning?

The walking inserts lift out to provide access to the bath interior. The B52672(0600) aluminium model has two treadplate panels with lifting holes to help with removal and a side drain outlet for emptying the bath.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357