
PRODUCT RANGE SPECIFICATION

B52672 – Footwear Sanitation Baths without Handrails



PRODUCT IMAGE · B52672(0600) aluminium treadplate model shown. The stainless steel grid model has a different insert.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B52672{PSS}	18 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b52672-sanitation-baths-with-aluminium-treadplate-inserts#specifications

01 Product description and specification

Product description

Floor-mounted Grade 304 stainless steel footwear sanitation baths without handrails, with removable aluminium treadplate or Grade 304 stainless steel grid inserts.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B52672. Floor-mounted footwear sanitation baths; Grade 304 stainless steel main construction; supplied without safety handrails; removable aluminium treadplate or Grade 304 stainless steel grid inserts. Available in one, two or three walkway widths according to model. Refer to the selected model for exact overall dimensions.

02 Configuration options

Removable Insert	Aluminium Treadplate; Grade 304 Stainless Steel Grid

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 **Grade 304 Stainless Steel Construction**
Stainless steel main construction provides a durable bath for repeated use at production entrances.

02 **Removable Walking Inserts**
Aluminium treadplate or Grade 304 stainless steel grid inserts lift out to provide access to the bath interior for cleaning.

03 **Adjustable Feet for Levelling**
The B52672(0600) aluminium model has four screw-adjustable feet for levelling the bath during installation.

04 **Walkway Width Options**
One, two or three walkway widths let you match the bath to the entrance layout and number of walkways required.

05 **Drain Outlet for Solution Changes**
The B52672(0600) aluminium model has a low-level side outlet that provides a drainage point for solution changes and cleaning.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Application information

Intended applications	Footwear Cleaning and Disinfection
Industries	Food & Beverage Processing, Meat & Poultry Processing

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

What is the B52672 range used for?

B52672 baths provide a defined footwear sanitation point at work-area entrances and transitions into production areas, as part of the site footwear hygiene procedure. Applications include food and beverage facilities, meat and poultry processing areas, and changing-room exits leading into production.

What is the difference between B52672 and B52673?

B52672 is supplied without safety handrails. B52673 is the corresponding range with safety handrails. Both ranges offer removable aluminium treadplate or Grade 304 stainless steel grid inserts.

Which removable inserts can I choose?

Choose removable aluminium treadplate inserts or a removable Grade 304 stainless steel grid insert. The listed single-walkway models are B52672(0600) with aluminium treadplate and B52672(0600G) with a stainless steel grid.

What material is used for the bath construction?

The main construction is Grade 304 stainless steel. The treadplate inserts are aluminium, while the stainless steel grid option is also Grade 304.

Which walkway widths are available?

The range is available in one, two and three walkway widths. The two listed models are the single-walkway versions. Contact Basterfield for the wider configurations and their model-specific dimensions and pricing.

What are the overall dimensions of B52672(0600)?

Overall outside dimensions are 689mm (L) x 602mm (W) x 187mm (H). The overall length includes the feet projection; the bath-body length is 642mm. Use the outside dimensions when planning the installation space. Overall height varies with foot adjustment.

How are the inserts, feet and drainage arranged on B52672(0600)?

The aluminium model has two removable treadplate panels with lifting holes, four screw-adjustable feet for levelling and a low-level side drain outlet for solution changes and cleaning. The outlet centre is 49mm above the floor at the stated overall height.

How do I access the bath interior for cleaning?

The walking inserts lift out to provide access to the bath interior. The B52672(0600) aluminium model has two treadplate panels with lifting holes to help with removal and a side drain outlet for emptying the bath.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357