


PRODUCT RANGE SPECIFICATION

B52672 – Footwear Sanitation Baths without Handrails



PRODUCT IMAGE · B52672(0600) aluminium treadplate model shown. The stainless steel grid model has a different insert.

Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B52672{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

28 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/b52672-sanitation-baths-with-aluminium-treadplate-inserts#specifications>



01 Product description and specification

Product description

Floor-mounted Grade 304 stainless steel footwear sanitation baths without handrails, with removable aluminium treadplate or Grade 304 stainless steel grid inserts.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B52672. Floor-mounted footwear sanitation baths; Grade 304 stainless steel main construction; supplied without safety handrails; removable aluminium treadplate or Grade 304 stainless steel grid inserts. Available in one, two or three walkway widths according to model. Refer to the selected model for exact overall dimensions.

02 Configuration options

Removable Insert

Aluminium Treadplate; Grade 304 Stainless Steel Grid

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 Grade 304 Stainless Steel Construction

Stainless steel main construction provides a durable bath for repeated use at production entrances.

02 Removable Walking Inserts

Aluminium treadplate or Grade 304 stainless steel grid inserts lift out to provide access to the bath interior for cleaning.

03 Adjustable Feet for Levelling

The B52672(0600) aluminium model has four screw-adjustable feet for levelling the bath during installation.

04 Walkway Width Options

One, two or three walkway widths let you match the bath to the entrance layout and number of walkways required.

05 Drain Outlet for Solution Changes

The B52672(0600) aluminium model has a low-level side outlet that provides a drainage point for solution changes and cleaning.

04 Application information

Intended applications	Footwear Cleaning and Disinfection
Industries	Food & Beverage Processing, Meat & Poultry Processing

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.