MODEL SPECIFICATION

B57110(FS-0500-050-2B) – Grease Trap 500x300x400, 304 SS, Front/Side 90°



PRODUCT IMAGE · Representative Front and Side (90°) layout shown on the larger model. Compact model: 500 × 300 × 400 mm with 50 mm connections.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B57110(FS-0500-050-2B){PSS}	12 Nov 2026

01 Model specification

Grease Trap Stainless Steel Grade 304 0.9mm Main-Body Thickness, 500mm (L) X 300mm (W) X 400mm (H) with Ø50mm Inlet and Outlet on the Front and Side at 90°, Two-Basket System, and Drop-On Lid with Handle

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Material Thickness	0.9	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Width	300	mm	The width of the item typically as measured from front to back.
Height	400	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Trap Basket Count	2	–	–
Primary Basket Perforation Diameter	6	mm	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Secondary Basket Perforation Diameter	3	mm	—
Drop-On Lid	With Handle	—	—
Inlet/Outlet Arrangement	Front and Side (90°)	—	Relative positions of the inlet and outlet on the grease-trap body.
Inlet Diameter	50	mm	—
Waste Outlet Diameter	50	mm	—

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	500	mm
Width	300	mm
Overall height	400	mm

04 Model and supply data

Parent product	B57110(0500) — Compact Two-Basket Grease Trap — 50 mm Connections
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

Compact grease trap suitable for single bowls and prep sinks. Grade 304 stainless steel with 0.9 mm main-body thickness, 500 mm (L) × 300 mm (W) × 400 mm (H). Diameter 50 mm inlet and outlet on the front and side at 90°. Two-basket system: primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations. Drop-on lid with handle. Images illustrate the layout using the larger model.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

Basterfield B57110(FS-0500-050-2B). Compact grease trap suitable for single bowls and prep sinks. Grade 304 stainless steel with 0.9 mm main-body thickness, 500 mm (L) × 300 mm (W) × 400 mm (H). Diameter 50 mm inlet and outlet on the front and side at 90°. Two-basket system: primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations. Drop-on lid with handle. Images illustrate the layout using the larger model.

Detailed specification

- Material: Stainless Steel Grade 304
- Material Thickness: 0.9 mm
- Width: 300 mm
- Waste Outlet Diameter: 50 mm
- Height: 400 mm
- Length: 500 mm
- Inlet Diameter: 50 mm
- Trap Basket Count: 2
- Primary Basket Perforation Diameter: 6 mm
- Secondary Basket Perforation Diameter: 3 mm
- Drop-On Lid: With Handle
- Inlet/Outlet Arrangement: Front and Side (90°)

06 Frequently asked questions

Which sinks is this grease trap suitable for?

This compact model is suitable for single bowls and prep sinks. Confirm the sink discharge flow and grease load when selecting a grease trap.

What are the dimensions and connection sizes?

The body measures 500 mm long, 300 mm wide and 400 mm high. Both the inlet and outlet are diameter 50 mm.

Which outlet layouts can I choose?

Choose Opposite Sides, Same Side (Front), or Front and Side (90°). These are three alternative layouts for one inlet and one outlet.

What material and thickness are used?

Grade 304 stainless steel with a 0.9 mm main-body thickness.

What are the two basket perforation sizes?

The primary basket has diameter 6 mm perforations and the secondary basket has diameter 3 mm perforations.

What access is needed for cleaning?

A drop-on lid with a handle is supplied. Allow access above the unit to lift the lid and remove the baskets for cleaning.

Is another body size available?

Yes. Choose the larger 700 × 400 × 400 mm model with 110 mm connections for large format sinks and pot sinks. The two sizes each offer the same three outlet-layout choices.

What does the item code mean?

In B57110(OS-0500-050-2B), OS identifies opposite sides, 0500 identifies the 500 mm length, 050 identifies the 50 mm connections, and 2B identifies the two-basket system. FF identifies both connections on the front; FS identifies front-and-side connections at 90°. Grade 304 stainless steel and 0.9 mm main-body thickness are fixed specifications.

Are the images of this exact body size?

The images show the larger model to illustrate the three outlet layouts. This compact model measures 500 × 300 × 400 mm and has diameter 50 mm inlet and outlet connections.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357