PRODUCT RANGE SPECIFICATION

B57110(0500) – Compact Two-Basket Grease Trap — 50 mm Connections



PRODUCT IMAGE · Representative Opposite Sides layout shown on the larger model. Compact model: 500 × 300 × 400 mm with 50 mm connections.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B57110(0500){PSS}	11 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b571100500-compact-two-basket-grease-trap-50-mm-connections#specifications

01 Product description and specification

Product description

Compact Two-Basket Grease Trap for single bowls and prep sinks. Grade 304 stainless steel, 500 × 300 × 400 mm, with 50 mm connections and three outlet-layout choices.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B57110(0500). Grease trap, Grade 304 stainless steel, 0.9 mm main-body thickness, 500 × 300 × 400 mm (L × W × H), with diameter 50 mm inlet and outlet, two perforated baskets (primary 6 mm, secondary 3 mm), and drop-on lid with handle. Specify opposite sides, same side (front), or front and side (90°). Suitable for single bowls and prep sinks.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Width	300	mm	The width of the item typically as measured from front to back.
Waste Outlet Diameter	50	mm	–

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Height	400	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Length	500	mm	The length of the item typically as measured from left to right.
Inlet Diameter	50	mm	–
Trap Basket Count	2	–	–
Primary Basket Perforation Diameter	6	mm	–
Secondary Basket Perforation Diameter	3	mm	–
Drop-On Lid	With Handle	–	–

03 Configuration options

Outlet Configuration	Front and Side (90°); Opposite Sides; Same Side (Front)

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 For Single Bowls and Prep Sinks
500 × 300 × 400 mm body with diameter 50 mm connections, suitable for single bowls and prep sinks.

02 Three Outlet Layouts
Opposite sides, both connections on the front, or front and side at 90°.

03 Grade 304 Stainless Steel
Grade 304 stainless steel construction with a 0.9 mm main-body thickness.

04 Two-Basket System
Primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations.

05 Drop-On Lid with Handle
Lift-off lid and removable baskets provide access for cleaning.

05 Application information

Intended applications	Drainage & Wastewater Management, Kitchen Washing & Warewashing
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

07 Frequently asked questions

Which sinks is this grease trap suitable for?

This compact model is suitable for single bowls and prep sinks. Confirm the sink discharge flow and grease load when selecting a grease trap.

What are the dimensions and connection sizes?

The body measures 500 mm long, 300 mm wide and 400 mm high. Both the inlet and outlet are diameter 50 mm.

Which outlet layouts can I choose?

Choose Opposite Sides, Same Side (Front), or Front and Side (90°). These are three alternative layouts for one inlet and one outlet.

What material and thickness are used?

Grade 304 stainless steel with a 0.9 mm main-body thickness.

What are the two basket perforation sizes?

The primary basket has diameter 6 mm perforations and the secondary basket has diameter 3 mm perforations.

What access is needed for cleaning?

A drop-on lid with a handle is supplied. Allow access above the unit to lift the lid and remove the baskets for cleaning.

Is another body size available?

Yes. Choose the larger 700 × 400 × 400 mm model with 110 mm connections for large format sinks and pot sinks. The two sizes each offer the same three outlet-layout choices.

What does the item code mean?

In B57110(OS-0500-050-2B), OS identifies opposite sides, 0500 identifies the 500 mm length, 050 identifies the 50 mm connections, and 2B identifies the two-basket system. FF identifies both connections on the front; FS identifies front-and-side connections at 90°. Grade 304 stainless steel and 0.9 mm main-body thickness are fixed specifications.

Are the images of this exact body size?

The images show the larger model to illustrate the three outlet layouts. This compact model measures 500 × 300 × 400 mm and has diameter 50 mm inlet and outlet connections.

Product drawings and images



PRODUCT IMAGE · Representative Same Side (Front) layout shown on the larger model. Compact model: 500 × 300 × 400 mm with 50 mm connections.



PRODUCT IMAGE · Representative Front and Side (90°) layout shown on the larger model. Compact model: 500 × 300 × 400 mm with 50 mm connections.

E&OE. Specifications are subject to change without notice.