MODEL SPECIFICATION

B57110(FF-0700-110-2B) – Grease Trap Stainless Steel Grade 304 0.9mm Main-Body Thickness, 700mm (L) X 400mm (W) X 400mm (H) with Ø110mm Inlet and Outlet on the Same Side (Front), Two-Basket System, and Drop-On Lid with Handle

PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B57110(FF-0700-110-2B){PSS}	Published catalogue data	1 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	Main-body stainless steel thickness. Basket perforation diameters are specified separately.
Width	400	mm	The width of the item typically as measured from front to back.
Waste Outlet Diameter	110	mm	–
Height	400	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Length	700	mm	The length of the item typically as measured from left to right.
Inlet Diameter	110	mm	–
Trap Basket Count	2	–	–
Primary Basket Perforation Diameter	6	mm	–
Secondary Basket Perforation Diameter	3	mm	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Drop-On Lid	With Handle	—	—
Inlet/Outlet Arrangement	Same Side (Front)	—	Relative positions of the inlet and outlet on the grease-trap body.

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	700	mm
Width	400	mm
Overall height	400	mm

03 Model and supply data

Parent product	B57110(0700) — Large Two-Basket Grease Trap — 110 mm Connections
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

Suitable for large format sinks and pot sinks. Grade 304 stainless steel grease trap with 0.9 mm main-body thickness, 700 mm (L) x 400 mm (W) x 400 mm (H). Diameter 110 mm inlet and outlet on the same side (front). Two-basket system: primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations. Drop-on lid with handle.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B57110(FF-0700-110-2B). Grade 304 stainless steel grease trap with 0.9 mm main-body thickness, 700 mm (L) x 400 mm (W) x 400 mm (H). Diameter 110 mm inlet and outlet on the same side (front). Two-basket system: primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations. Drop-on lid with handle.

Detailed specification

- Material: Stainless Steel Grade 304
- Length: 700 mm
- Width: 400 mm
- Height: 400 mm
- Inlet Diameter: 110 mm
- Waste Outlet Diameter: 110 mm
- Trap Basket Count: 2
- Primary Basket Perforation Diameter: 6 mm
- Secondary Basket Perforation Diameter: 3 mm
- Drop-On Lid: With Handle
- Main-Body Thickness: 0.9 mm
- Inlet/Outlet Arrangement: Same Side (Front)

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357