MODEL SPECIFICATION

# B57110(FF-0700-110-2B) – Grease Trap 700x400x400, 304 SS, Same-Side



PRODUCT IMAGE

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | B57110(FF-0700-110-2B){PSS} | 11 Nov 2026 |

## 01 Model specification

Grease Trap Stainless Steel Grade 304 0.9mm Main-Body Thickness, 700mm (L) X 400mm (W) X 400mm (H) with Ø110mm Inlet and Outlet on the Same Side (Front), Two-Basket System, and Drop-On Lid with Handle

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| Material | Stainless Steel Grade 304 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| Material Thickness | 0.9 | mm | Main-body stainless steel thickness. Basket perforation diameters are specified separately. |
| Width | 400 | mm | The width of the item typically as measured from front to back. |
| Waste Outlet Diameter | 110 | mm | – |
| Height | 400 | mm | Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height. |
| Length | 700 | mm | The length of the item typically as measured from left to right. |
| Inlet Diameter | 110 | mm | – |
| Trap Basket Count | 2 | – | – |
| Primary Basket Perforation Diameter | 6 | mm | – |

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| Secondary Basket Perforation Diameter | 3 | mm | — |
| Drop-On Lid | With Handle | — | — |
| Inlet/Outlet Arrangement | Same Side (Front) | — | Relative positions of the inlet and outlet on the grease-trap body. |

## 03 Dimensions and mass

| PARAMETER | VALUE | UNIT |
|---|---|---|
| Length | 700 | mm |
| Width | 400 | mm |
| Overall height | 400 | mm |

## 04 Model and supply data

| | |
|---|---|
| Parent product | B57110(0700) — Large Two-Basket Grease Trap — 110 mm Connections |
| Typical lead time | 10–15 working days |
| Warranty | 12 months |

## 05 Specification notes

**Configuration description**

Suitable for large format sinks and pot sinks. Grade 304 stainless steel grease trap with 0.9 mm main-body thickness, 700 mm (L) x 400 mm (W) x 400 mm (H). Diameter 110 mm inlet and outlet on the same side (front). Two-basket system: primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations. Drop-on lid with handle.

**Short Form Specification**

> **SPECIFICATION USE**
> Use this description when specifying this model.

Basterfield B57110(FF-0700-110-2B). Grade 304 stainless steel grease trap with 0.9 mm main-body thickness, 700 mm (L) x 400 mm (W) x 400 mm (H). Diameter 110 mm inlet and outlet on the same side (front). Two-basket system: primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations. Drop-on lid with handle.

**Detailed specification**

- Material: Stainless Steel Grade 304
- Length: 700 mm
- Width: 400 mm
- Height: 400 mm
- Inlet Diameter: 110 mm
- Waste Outlet Diameter: 110 mm
- Trap Basket Count: 2
- Primary Basket Perforation Diameter: 6 mm
- Secondary Basket Perforation Diameter: 3 mm
- Drop-On Lid: With Handle
- Main-Body Thickness: 0.9 mm
- Inlet/Outlet Arrangement: Same Side (Front)

## 06 Frequently asked questions

**Which sinks is this grease trap suitable for?**

This larger model is suitable for large format sinks and pot sinks. Confirm the sink discharge flow and grease load when selecting a grease trap.

**What are the dimensions and connection sizes?**

The body measures 700 mm long, 400 mm wide and 400 mm high. Both the inlet and outlet are diameter 110 mm.

**Which outlet layouts can I choose?**

Choose Opposite Sides, Same Side (Front), or Front and Side (90°). These are three alternative layouts for one inlet and one outlet.

**What material and thickness are used?**

Grade 304 stainless steel with a 0.9 mm main-body thickness.

**What are the two basket perforation sizes?**

The primary basket has diameter 6 mm perforations and the secondary basket has diameter 3 mm perforations.

**What access is needed for cleaning?**

A drop-on lid with a handle is supplied. Allow access above the unit to lift the lid and remove the baskets for cleaning.

**Is another body size available?**

Yes. Choose the compact 500 × 300 × 400 mm model with 50 mm connections for single bowls and prep sinks. The two sizes each offer the same three outlet-layout choices.

**What does the item code mean?**

In B57110(OS-0700-110-2B), OS identifies opposite sides, 0700 identifies the 700 mm length, 110 identifies the 110 mm connections, and 2B identifies the two-basket system. FF identifies both connections on the front; FS identifies front-and-side connections at 90°. Grade 304 stainless steel and 0.9 mm main-body thickness are fixed specifications.

E&OE. Specifications are subject to change without notice.