

PRODUCT RANGE SPECIFICATION

B57110(0700) – Large Two-Basket Grease Trap – 110 mm Connections



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
B57110(0700){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
1 Oct 2026

01 Product description and specification

Product description

The Basterfield B57110(0700) large two-basket grease trap is suitable for large format sinks and pot sinks. It measures 700 × 400 × 400 mm (L × W × H) and has diameter 110 mm inlet and outlet connections.

Grade 304 stainless steel construction uses a 0.9 mm main-body thickness. The two-basket system has a primary basket with diameter 6 mm perforations and a secondary basket with diameter 3 mm perforations. A drop-on lid with a handle provides access from above.

Choose one of three inlet/outlet layouts: opposite sides; both connections on the same side (front); or front and side at 90° to each other. Each configuration has one inlet and one outlet.

The range also includes a compact 500 × 300 × 400 mm model with 50 mm connections for single bowls and prep sinks. Confirm the sink discharge flow, grease load, pipe connections and installation space when selecting a model.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B57110(0700). Grease trap, Grade 304 stainless steel, 0.9 mm main-body thickness, 700 × 400 × 400 mm (L × W × H), with diameter 110 mm inlet and outlet, two perforated baskets (primary 6 mm, secondary 3 mm), and drop-on lid with handle. Specify opposite sides, same side (front), or front and side (90°). Suitable for large format sinks and pot sinks.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	Main-body stainless steel thickness. Basket perforation diameters are specified separately.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Width	400	mm	The width of the item typically as measured from front to back.
Waste Outlet Diameter	110	mm	—
Height	400	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Length	700	mm	The length of the item typically as measured from left to right.
Inlet Diameter	110	mm	—
Trap Basket Count	2	—	—
Primary Basket Perforation Diameter	6	mm	—
Secondary Basket Perforation Diameter	3	mm	—
Drop-On Lid	With Handle	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B57110(FF-0700-110-2B)	Grease Trap Stainless Steel Grade 304 0.9mm Main-Body Thickness, 700mm (L) X 400mm (W) X 400mm (H) with Ø110mm Inlet and Outlet on the Same Side (Front), Two-Basket System, and Drop-On Lid with Handle	Inlet/Outlet Arrangement: Same Side (Front) Overall dimensions: 700 × 400 × 400 mm (L × W × H)
B57110(FS-0700-110-2B)	Grease Trap Stainless Steel Grade 304 0.9mm Main-Body Thickness, 700mm (L) X 400mm (W) X 400mm (H) with Ø110mm Inlet and Outlet on the Front and Side at 90°, Two-Basket System, and Drop-On Lid with Handle	Inlet/Outlet Arrangement: Front and Side (90°) Overall dimensions: 700 × 400 × 400 mm (L × W × H)
B57110(OS-0700-110-2B)	Grease Trap Stainless Steel Grade 304 0.9mm Main-Body Thickness, 700mm (L) X 400mm (W) X 400mm (H) with Ø110mm Inlet and Outlet on Opposite Sides, Two-Basket System, and Drop-On Lid with Handle	Inlet/Outlet Arrangement: Opposite Sides Overall dimensions: 700 × 400 × 400 mm (L × W × H)

04 Functional features

- 01 For Large Format Sinks and Pot Sinks

700 × 400 × 400 mm body with diameter 110 mm connections, suitable for large format sinks and pot sinks.
- 02 Three Outlet Layouts

Opposite sides, both connections on the front, or front and side at 90°.
- 03 Grade 304 Stainless Steel

Grade 304 stainless steel construction with a 0.9 mm main-body thickness.

04 Two-Basket System

Primary basket with diameter 6 mm perforations and secondary basket with diameter 3 mm perforations.

05 Drop-On Lid with Handle

Lift-off lid and removable baskets provide access for cleaning.

05 Application information

Intended applications	Drainage & Wastewater Management, Kitchen Washing & Warewashing
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE · Same Side (Front)



PRODUCT IMAGE · Front and Side (90°)

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.