MODEL SPECIFICATION

B60140(600) – Cleaner's Sink, 600 x 500 mm, 230 mm Bowl



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B60140(600){PSS}	14 Nov 2026

01 Model specification

Wall-Mounted Grade 304 Stainless Steel Cleaner's Sink, 600 mm (L) x 500 mm (W), with 230 mm Bowl Depth, Hinged Bucket Grid, Rubber Bumpers and 40 mm Waste Outlet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	600	mm	The length of the item typically as measured from left to right.
Depth (mm)	230	mm	–
Width	500	mm	The width of the item typically as measured from front to back.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	–	–
Waste Outlet Diameter	40	mm	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	600	mm
Width	500	mm

04 Model and supply data

Parent product	B60140 — Wall-Mounted Stainless Steel Cleaner's Sink with Bucket Grid

04 Model and supply data

Typical lead time	10–15 working days
Warranty	24 months

05 Specification notes

Configuration description

Wall-mounted Grade 304 stainless steel cleaner's sink, 600 mm (L) x 500 mm (W), with 230 mm bowl depth, hinged bucket grid, rubber bumpers and 40 mm waste outlet.

Standard 230 mm bowl depth. The deep-drawn bowl has coved corners, and gallows brackets provide wall mounting. The hinged grid supports a bucket above the bowl and lifts for access.

Use the sink as a dedicated washing point for buckets and cleaning equipment in janitorial, housekeeping and utility rooms. Bowl depth is measured vertically within the bowl. Coordinate the installation height, wall support, water fittings and waste connection, and allow clearance for buckets and for raising the grid.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

Basterfield B60140(600). Wall-mounted Grade 304 stainless steel cleaner's sink, 600 mm (L) x 500 mm (W), with 230 mm bowl depth, hinged bucket grid, rubber bumpers and 40 mm waste outlet. Standard 230 mm bowl depth. Supplied with gallows mounting brackets. Coordinate wall support, mounting position and plumbing connections.

Detailed specification

Model: B60140(600)
Material: Stainless Steel Grade 304
Length: 600 mm
Width (front to back): 500 mm
Bowl depth: 230 mm
Configuration: Standard
Mounting: Wall mounted on gallows brackets
Bucket grid: Hinged grid included
Rubber bumpers: Included
Waste outlet diameter: 40 mm

06 Frequently asked questions

What size options are available?

Choose 480 or 600 mm length x 500 mm width. 230 mm bowl depth is standard. Enable advanced customisation to choose a 300 mm bowl depth.

What is the specification of B60140(600)?

B60140(600) is 600 mm long and 500 mm wide, with the standard 230 mm bowl depth. It is wall mounted and includes a hinged bucket grid, rubber bumpers and a 40 mm waste outlet. For a 300 mm bowl depth, enable advanced customisation and select B60140(600x300).

Is the bucket grid included?

Yes. A hinged bucket grid is included on the four listed B60140 configurations.

Does bowl depth mean the front-to-back size?

No. Bowl depth is the vertical depth of the bowl. The front-to-back width is 500 mm. Set the installation height above the floor separately.

How is the sink mounted and connected?

The sink is wall mounted on gallows brackets. Confirm wall support, fixing details, mounting height, water supply fittings and the 40 mm waste connection for the site.

Where can the cleaner's sink be used?

Use it in janitorial and housekeeping rooms and dedicated cleaning support areas at hospitality, healthcare, education, catering, laundry, laboratory and industrial premises.

How should the sink be cleaned?

Use cleaning products and methods suitable for Grade 304 stainless steel. Raise the hinged grid for access and follow the facility cleaning procedure.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357