

MODEL SPECIFICATION

B60140(600x300) – Wall-Mounted Grade 304 Stainless Steel Cleaner's Sink, 600 mm (L) x 500 mm (W), with 300 mm Bowl Depth, Hinged Bucket Grid, Rubber Bumpers and 40 mm Waste Outlet.



PRODUCT IMAGE

DOCUMENT SCOPE

Model

DOCUMENT REFERENCE

B60140(600x300){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	600	mm	The length of the item typically as measured from left to right.
Depth (mm)	300	mm	—

02 Model and supply data

Parent product	B60140 – Wall-Mounted Stainless Steel Cleaner's Sink with Bucket Grid
Typical lead time	10–15 working days
Warranty	24 months

03 Specification notes

Configuration description

Wall-mounted Grade 304 stainless steel cleaner's sink, 600 mm (L) x 500 mm (W), with 300 mm bowl depth, hinged bucket grid, rubber bumpers and 40 mm waste outlet.

Advanced customisation with 300 mm bowl depth. The deep-drawn bowl has coved corners, and gallows brackets provide wall mounting. The hinged grid supports a bucket above the bowl and lifts for access.

Use the sink as a dedicated washing point for buckets and cleaning equipment in janitorial, housekeeping and utility rooms. Bowl depth is measured vertically within the bowl. Coordinate the installation height, wall support, water fittings and waste connection, and allow clearance for buckets and for raising the grid.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this model.

Basterfield B60140(600x300). Wall-mounted Grade 304 stainless steel cleaner's sink, 600 mm (L) x 500 mm (W), with 300 mm bowl depth, hinged bucket grid, rubber bumpers and 40 mm waste outlet. Advanced customisation with 300 mm bowl depth. Supplied with gallows mounting brackets. Coordinate wall support, mounting position and plumbing connections.

Detailed specification	Model: B60140(600x300) Material: Stainless Steel Grade 304 Length: 600 mm Width (front to back): 500 mm Bowl depth: 300 mm Configuration: Advanced customisation Mounting: Wall mounted on gallows brackets Bucket grid: Hinged grid included Rubber bumpers: Included Waste outlet diameter: 40 mm
------------------------	---

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.