

MODEL SPECIFICATION

B65166(S3-1PL) – Boot Washer 1P Three Station

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B65166(S3-1PL){PSS}	Published catalogue data	26 Oct 2026

01 Model specification

B65166(1P) Manual Boot Washer. Three Stations; Left Hand Waste Outlet. Each Station Has Two Angled Side Brushes and a Hand-Held Water-Fed Scrubbing Brush for Manual Boot Cleaning.

Water Flow Is Controlled by a Mixer Lever That Can Be Operated by Hand or Wrist. Wrist Operation Can Reduce Direct Hand Contact with the Lever. The Current Design Uses a Mixer Rather than a Push-Button Valve.

The Main Body, Structural Frame, Handrails and Wetted Surfaces of the Wash Enclosure Are Grade 304 Stainless Steel. The Non-Wetted Rear Cover Panel Is Galvanised Mild Steel, the Internal Water Pipework Is Copper, and Proprietary Valves and Fittings May Have a Chrome-Plated Finish. Brushes and Other Functional Components Use Materials Appropriate to Their Function. The Complete Assembly Is Not Manufactured Entirely from Grade 304 Stainless Steel.

The Standard Waste Outlet Is 1½-Inch BSP with a BSPT Tapered Thread. Outlet Position Is Specified by the Selected Station Configuration.

Connect to a Normal Reticulated Water Supply. A Nominal Supply Pressure of Approximately 300 kPa Is Recommended. Pressure at the Mixer Must Not Exceed 600 kPa; Install a Suitable Pressure-Reducing Valve Where the Site Pressure Exceeds This Limit.

The Unit Is Freestanding on Adjustable Feet for Levelling. Where Required, the Adjustable Footplates May Be Anchored to the Floor to Secure the Unit.

Normal Use Allows One User per Station to Rest One Foot on the Unit During Cleaning. The Unit Is Designed to Support the Loads Imposed Under These Normal Operating Conditions. Users Must Not Stand or Climb on the Unit. No Separately Certified Maximum User-Load Rating Has Been Established. The Product Is Warranted for Its Intended Use Under Normal Operating Conditions.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Waste Outlet Orientation	Left Hand	–	Determined by the number of stations: centre outlet for one station; left-hand outlet for two, three or four stations.
Number of Stations / Spouts	Three	–	Choose one, two, three or four stations. Waste outlet position follows the selected station count automatically.

03 Model and supply data

Parent product	B65166(1P) – Manual Boot Washer with Angled Side Brushes
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	Each station has two angled side brushes and a hand-held water-fed scrubbing brush for manual boot cleaning. Water operation Water flow is controlled by a mixer lever that can be operated by hand or wrist. Wrist operation can reduce direct hand contact with the lever. The current design uses a mixer rather than a push-button valve. Materials The main body, structural frame, handrails and wetted surfaces of the wash enclosure are Grade 304 stainless steel. The non-wetted rear cover panel is galvanised mild steel, the internal water pipework is copper, and proprietary valves and fittings may have a chrome-plated finish. Brushes and other functional components use materials appropriate to their function. The complete assembly is not manufactured entirely from Grade 304 stainless steel. Waste connection The standard waste outlet is 1½-inch BSP with a BSPT tapered thread. Outlet position is specified by the selected station configuration. Operating water pressure Connect to a normal reticulated water supply. A nominal supply pressure of approximately 300 kPa is recommended. Pressure at the mixer must not exceed 600 kPa; install a suitable pressure-reducing valve where the site pressure exceeds this limit. Installation The unit is freestanding on adjustable feet for levelling. Where required, the adjustable footplates may be anchored to the floor to secure the unit. Intended use and operating load Normal use allows one user per station to rest one foot on the unit during cleaning. The unit is designed to support the loads imposed under these normal operating conditions. Users must not stand or climb on the unit. No separately certified maximum user-load rating has been established. The product is warranted for its intended use under normal operating conditions. Selected configuration: Three stations; left hand waste outlet.
---------------------------	---

Short Form Specification	SPECIFICATION USE Use this description when specifying this model. B65166(1P); Three stations; left hand waste outlet. Each station has two angled side brushes and a hand-held water-fed scrubbing brush for manual boot cleaning. Grade 304 stainless steel body, frame, handrails and wash enclosure; galvanised rear cover; copper internal pipework. Hand-/wrist-operated mixer. 1½-inch BSPT waste. Approximately 300 kPa recommended supply; maximum 600 kPa at mixer. Freestanding on adjustable feet; footplates may be anchored. One foot resting per user per station; no standing or climbing; no separately certified maximum user-load rating.
--------------------------	---

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.