

MODEL SPECIFICATION

B65166(S1-112-2PC) – B65166(2P) manual boot washer. Overall dimensions: 610 mm (L) x 650 mm (W) x 1100 mm (H). One station; centre waste outlet. Each station has fixed brushes for cleaning boot soles and a hand-held water-fed scrubbing brush for the sides and uppers. The fixed brush arrangement is for sole cleaning only. Water flow is controlled by a mixer lever that can be operated by hand or wrist. Wrist operation can reduce direct hand contact with the lever. The current design uses a mixer rather than a push-button valve. The main body, structural frame, handrails and wetted surfaces of the wash enclosure are Grade 304 stainless steel. The non-wetted rear cover panel is galvanised mild steel, the internal water pipework is copper, and proprietary valves and fittings may have a chrome-plated finish. Brushes and other functional components use materials appropriate to their function. The complete assembly is not manufactured entirely from Grade 304 stainless steel. The standard waste outlet is 1½-inch BSP with a BSPT tapered thread. Outlet position is specified by the selected station configuration. Connect to a normal reticulated water supply. A nominal supply pressure of approximately 300 kPa is recommended. Pressure at the mixer must not exceed 600 kPa; install a suitable pressure-reducing valve where the site pressure exceeds this limit. The unit is freestanding on adjustable feet for levelling. Where required, the adjustable footplates may be anchored to the floor to secure the unit. Normal use allows one user per station to rest one foot on the unit during cleaning. The unit is designed to support the loads imposed under these normal operating conditions. Users must not stand or climb on the unit. No separately certified maximum user-load rating has been established. The product is warranted for its intended use under normal operating conditions.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B65166(S1-112-2PC){PSS}	Published catalogue data	16 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Number of Stations / Spouts	One	—	Choose one, two, three or four stations. Waste outlet position follows the selected station count automatically.
Waste Outlet Orientation	Centre	—	Determined by the number of stations: centre outlet for one station; left-hand outlet for two, three or four stations.

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	610	mm
Width	650	mm
Height	1100	mm

03 Model and supply data

Parent product	B65166(2P) – Manual Boot Washer with Sole Brushes
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	Each station has fixed brushes for cleaning boot soles and a hand-held water-fed scrubbing brush for the sides and uppers. The fixed brush arrangement is for sole cleaning only. Water operation Water flow is controlled by a mixer lever that can be operated by hand or wrist. Wrist operation can reduce direct hand contact with the lever. The current design uses a mixer rather than a push-button valve. Materials The main body, structural frame, handrails and wetted surfaces of the wash enclosure are Grade 304 stainless steel. The non-wetted rear cover panel is galvanised mild steel, the internal water pipework is copper, and proprietary valves and fittings may have a chrome-plated finish. Brushes and other functional components use materials appropriate to their function. The complete assembly is not manufactured entirely from Grade 304 stainless steel. Waste connection The standard waste outlet is 1½-inch BSP with a BSPT tapered thread. Outlet position is specified by the selected station configuration. Operating water pressure Connect to a normal reticulated water supply. A nominal supply pressure of approximately 300 kPa is recommended. Pressure at the mixer must not exceed 600 kPa; install a suitable pressure-reducing valve where the site pressure exceeds this limit. Installation The unit is freestanding on adjustable feet for levelling. Where required, the adjustable footplates may be anchored to the floor to secure the unit. Intended use and operating load Normal use allows one user per station to rest one foot on the unit during cleaning. The unit is designed to support the loads imposed under these normal operating conditions. Users must not stand or climb on the unit. No separately certified maximum user-load rating has been established. The product is warranted for its intended use under normal operating conditions. Selected configuration: One station; centre waste outlet. Overall dimensions: 610 mm (L) x 650 mm (W) x 1100 mm (H).
---------------------------	--

Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Overall dimensions: 610 mm (L) x 650 mm (W) x 1100 mm (H). B65166(2P); One station; centre waste outlet. Each station has fixed brushes for cleaning boot soles and a hand-held water-fed scrubbing brush for the sides and uppers. The fixed brush arrangement is for sole cleaning only. Grade 304 stainless steel body, frame, handrails and wash enclosure; galvanised rear cover; copper internal pipework. Hand-/wrist-operated mixer. 1½-inch BSPT waste. Approximately 300 kPa recommended supply; maximum 600 kPa at mixer. Freestanding on adjustable feet; footplates may be anchored. One foot resting per user per station; no standing or climbing; no separately certified maximum user-load rating.
--------------------------	--

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.