

MODEL SPECIFICATION

B65210(R) – Single Boot Scrubber
Motorised, 380 V Three-Phase.



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
B65210(R){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT
Electrical Supply Option	380 V three-phase	—

02 Model and supply data

Parent product	B65210(R) – Wall-Mounted Automatic Boot Scrubber
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description

Single-station wall-mounted motorised boot scrubber for cleaning footwear at production-area entrances.

Key features of the B65210 Wall Mounted Motorised Boot Scrubber Single Station include:

- Constructed from durable stainless steel Grade 304.
- Wall Mounted design allows for easy cleaning underneath and optimal use of limited space.
- Single station equipped with a motorised boot scrubbing brush for efficient cleaning.
- Standard brushware effectively cleans both sole and sides of boots.
- Solenoid activated water flow ensures a controlled and efficient clean.
- In-line venturi based automated soap/chemical dosing system for hassle-free sanitization.
- Stainless steel threaded waste outlet allows for easy connection to drainage systems.
- This B65210(R) item is the 380 V three-phase configuration. The B65210 range is also available in 220 V single-phase; specify the required supply when requesting a quotation.
- Compact dimensions measuring approximately 600 mm (L) x 300 mm (W) x 1100 mm (H).

Short Form Specification

SPECIFICATION USE

Use this description when specifying this model.

Basterfield B65210(R) single-station wall-mounted motorised boot scrubber, Grade 304 stainless steel. Approximate overall dimensions 600 x 300 x 1100 mm. Electrical supply: 380 V three-phase. Confirm installation requirements for the selected unit.

Detailed specification

- Model: B65210(R)
- Constructed from durable stainless steel Grade 304
- Stainless steel threaded waste outlet allows for easy connection to drainage systems
- Compact dimensions measuring approximately 600 mm (L) x 300 mm (W) x 1100 mm (H)
- Electrical supply: 380 V three-phase

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.