

PRODUCT RANGE SPECIFICATION

B65230 – Single-Station Motorised Boot Scrubber



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B65230{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

24 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/b65230-boot-scrubber-motorised-single-station#specifications>



01 Product description and specification

Product description

A durable boot-cleaning station that helps staff remove dirt from soles and lower sides before entering production areas. Brushing, water and soap work together in one simple routine, with straightforward controls and adjustable soap dosing to suit your cleaning process.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B65230. Grade 304 stainless steel single-user boot scrubber for one boot at a time; sole and lower side brushing; robust bristles and protective grid; manual on/off operation; 0.37kW motor with built-in motor starter protection; 1/2" solenoid water control; adjustable inline peristaltic soap dosing; isolator, emergency stop and power/running pilot lights; 1 1/2" BSP drainage outlet at the bottom rear of the trough. Electrical options: 220V single-phase or 380V three-phase.

02 Configuration options

Electrical supply

220 V single-phase; 380 V three-phase

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 Sole and Lower Side Brushing

A single station cleans the sole and lower sides of one boot at a time. One user operates the machine at a time.

02 Hard-Wearing Bristles and Protective Grid

Robust bristles provide hard-wearing brushing, with a protective grid fitted over the brushing area.

03 Manual On/Off Operation

Switching the unit on starts brush rotation, activates water spray onto the brushes and starts inline soap dosing together.

04 Adjustable Peristaltic Soap Dosing

A peristaltic pump introduces soap into the water line. Its adjustable flow rate allows the soap feed to be set for the cleaning process.

- 05

1/2" Solenoid Water Control

The 1/2" solenoid provides automatic water control during operation, supplying spray to the brushes when the unit is switched on.
- 06

0.37kW Motor with Starter Protection

A 0.37kW motor drives the brushes. A built-in motor starter provides motor protection.
- 07

Isolator, Emergency Stop and Pilot Lights

An isolator and emergency stop are provided. Separate pilot lights indicate that power is available and that the unit is running.
- 08

1 1/2" BSP Rear Drainage Outlet

The trough drains through a 1 1/2" BSP outlet positioned at its bottom rear, providing a defined drainage connection.

04 Application information

Intended applications	Footwear Cleaning and Disinfection
Industries	Dairy & Beverage Processing, Fish & Seafood Processing, Food & Beverage Processing, Fresh Produce & Packhouses, Meat & Poultry Processing

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.